		WATE	R WELL RECORD	Form WW	C-5 KSA 828	a-1212		
LOCATION OF WATER V	Δ	Fraction	\$12 <	ا ہے:	Section Number			Range Number
ounty: Walkuroc		1/4			36	T 25	<u> </u>	RILEN
distance and direction from	nearest town	or city street ac	dress of well if lo	cated within ci	ty?			M 111-92-2
			- A - /	1,10				NW-93-3
WATER WELL OWNER	u vel	wwood	Coi Lou	uafill				Ð
RR#, St. Address, Box #	: 📈	1.	11	U		Board of	Agriculture, I	Division of Water Resources
City, State, ZIP Code	EW	ella,	Kansas	سربر ک	-	Applicati	on Number:	
LOCATE WELL'S LOCAT	x. —							
N		,	water Encountered	A / F				
	; w		WATER LEVEL .					
NW	NE	•						mping gpm
'Y'	Es	st. Yield	gpm; Well	water was	ft. a	after	hours pu	mping gpm
<u> </u>	I Bo	re Hole Diame	ter <i>[Q</i> .in	. to	.) ft.,	and	in.	to/ft.
w i	ı W	ELL WATER T	O BE USED AS:	5 Public v	vater supply	8 Air conditioning	ng 11	Injection well
. "	!	1 Domestic	3 Feedlot	6 Oil field	water supply	9 Dewatering	12	Other (Specify below)
2M	35	2 Irrigation	4 Industrial	7 Lawn a	nd garden only (10 Monitoring w	ell,	
	x w	as a chemical/b	acteriological sam	ple submitted t	o Department? Y	esNo	; If yes,	mo/day/yr sample was sub-
, ,		tted	•	•		ater Well Disinfed		No X
TYPE OF BLANK CASIN			5 Wrought iron	8 Co	ncrete tile			Clamped
1 Steel	3 RMP (SR)		6 Asbestos-Cem		her (specify below	w)	Weld	ed
2 AVC	4 ABS		7 Fiberglass					nded
Blank casing diameter	7	, 45						in. to ft.
•) /l .	in., weight	2.07		/ft. Wall thickness		
Casing height above land st			in., weight					• /
YPE OF SCREEN OR PE				\sim	PVC		sbestos-ceme	
1 Steel	3 Stainless st		5 Fiberglass		RMP (SR)			
2 Brass	4 Galvanized		6 Concrete tile	9	ABS		one used (op	en hole)
CREEN OR PERFORATION			5 G	Sauzed wrappe	d	8 Saw cut		11 None (open hole)
 Continuous slot 	(´3`M)ill s	slot		Vire wrapped		9 Drilled holes	6	
2 Louvered shutter	4 Key	punched	45 ^{7 T}	orch cut		10 Other (spec	ify)	
CREEN-PERFORATED IN	TERVALS:	From	ft. 1	to	ft., Fro	om	ft. t	o
		From	ft. ا	to	ft., Fro	m	ft. t	o
GRAVEL PACK IN	ITERVALS:	From	3 ft. ₁	to 5 . 5	ft., Fro			o
	_	From	ft.		ft., Fro		ft. t	
GROUT MATERIAL:	1 Neat cerr	nent .	2 Cement grout	л (3) _{Ве}	entonite , 4	Other		
Grout Intervals: From	D. ft.		ft., From	<i>/L</i> _/	71 7			ft. to ft.
Vhat is the nearest source			,,			stock pens		pandoned water well
1 Septic tank	4 Lateral li		7 Pit privy	,	11 Fuel	•		il well/Gas well
2 Sewer lines	5 Cess po		8 Sewage			•		
				•		lizer storage	16 0	ther (specify below)
3 Watertight sewer lin		" / L	9 Feedyar	ď		cticide storage		• • • • • • • • • • • • • • • • • • • •
Pirection from well?	10 m	LITHOLOGIC	200	FROM	How ma		PLUGGING II	ITEDVALO
A /	1/2400	LITHOLOGIG I	_06	FRON	1 TO		-LUGGING II	VIERVALS
0 6	rang							
1 0 1		~~~ ·						
6 8 6	3 /							
8 10 5	hale							
10 11,5 6	<u>ج۔</u>							
11 - 40 - 0	1. 1.							
11.5 42.5 8	hale							
		100						
12,5 44,5 6	-5 7 2	Shall						
4.5 47 L	.5							NIAL
			·				(10	MAL GA
47 1 77 1	Shell						15%	ENRIMIT
<u>' </u>	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,						141/8	PG 1514
77 74	/ -		,					101314 4 101
1 10 1							18	(6)
CONTRACTOR'S OR LA	NDOWNER'S	GERTIFICATIO	ON: This water we	ell was (1) con	structed, (2) reco	onstructed, or (3)	plugged und	my urisdiction and was
ompleted on (mo/day/year)		11718	.9.5			ord is true to the I		yledge and belief. Kaylsas
Vater Well Contractor's Lice	ense No,	10 4	∩ This Wat	er Well Record	was completed	on (mo/dex/yr)	. KAYA	ではる ノーノー
nder the business name of	Lo	usne,	EW_		by (signa	- X7:	n X W	Hitadl
INSTRUCTIONS: Use typewrite		PLE SE PRESE EI	RMLY and PRINT clear	lv. Please fill in bler			Send ton three	on Mkinsas Department
						WNER and retain one		