

1 LOCATION OF WATER WELL: County: Woodson, Fraction NW 1/4 NW 1/4 NW 1/4, Section Number 14, Township Number T 25 S, Range Number R 15 E/W

Distance and direction from nearest town or city street address of well if located within city? ~17.5'E/25'S of SE corner of W. Mary & S. Fry Sts.

2 WATER WELL OWNER: Crescent Oil Company, Inc. RR#, St. Address, Box #: PO Box 667, City, State, ZIP Code: Independence, Kansas 67301, Board of Agriculture, Division of Water Resources, Application Number:

3 LOCATE WELL'S LOCATION WITH AN 'X' IN SECTION BOX: [Map showing NW, NE, SW, SE sections with an 'X' in the NW section. Scale: 1 Mile]
4 DEPTH OF COMPLETED WELL: 14 ft. ELEVATION: 1111.57
Depth(s) Groundwater Encountered: 1. ft. 2. ft. 3. ft.
WELL'S STATIC WATER LEVEL: below land surface measured on mo/day/yr
Pump test data: Well water was NA ft. after hours pumping gpm
Est. Yield: NA gpm; Well water was ft. after hours pumping gpm
Bore Hole Diameter: 8 in. to 14 ft., and in. to ft.
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
Was a chemical/bacteriological sample submitted to Department? Yes.....No [checked] ; If yes, mo/day/yr sample was submitted
Water Well Disinfected? Yes No [checked]

5 TYPE OF BLANK CASING USED: 1 Steel 2 PVC [checked] 3 RMP (SR) 4 ABS 5 Wrought iron 6 Asbestos-Cement 7 Fiberglass 8 Concrete tile 9 Other (specify below) CASING JOINTS: Glued Clamped Welded Threaded [checked]
Blank casing diameter: 2 in. to 4 ft. Dia in. to ft. Dia in. to ft.
Casing height above land surface: -6.72 in., weight lbs./ft. Wall thickness or gauge No. Sch. 40
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 2 Brass 3 Stainless steel 4 Galvanized steel 5 Fiberglass 6 Concrete tile 7 PVC [checked] 8 RMP (SR) 9 ABS 10 Asbestos-cement 11 Other (specify) 12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 2 Louvered shutter 3 Mill slot [checked] 4 Key punched 5 Gauzed wrapped 6 Wire wrapped 7 Torch cut 8 Saw cut 9 Drilled holes 10 Other (specify) 11 None (open hole)
SCREEN-PERFORATED INTERVALS: From 4 ft. to 14 ft., From ft. to ft.
GRAVEL PACK INTERVALS: From 3 ft. to 14 ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement [checked] 2 Cement grout 3 Bentonite [checked] 4 Other
Grout Intervals: From 0 ft. to 1 ft., From 1 ft. to 3 ft., From ft. to ft.
What is the nearest source of possible contamination: 1 Septic tank 2 Sewer lines 3 Watertight sewer lines 4 Lateral lines 5 Cess pool 6 Seepage pit 7 Pit privy 8 Sewage lagoon 9 Feedyard 10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage 14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below)
Direction from well? How many feet?

LITHOLOGIC LOG table with columns FROM, TO, LITHOLOGIC LOG, FROM, TO, PLUGGING INTERVALS. Log entries: 0-0.5 Concrete, 0.5-5 Clay, silty, v. moist, Dark Gray Brown, 5-10 Shale, weathered, moist, Green, 10-14 Shale, weathered, Green Brown. Includes MW3R, Flushmount, Project Name: Carder's Philmart, GeoCore # 1199, KDHE # U3 104 00058

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9/17/2008 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 527. This Water Well Record was completed on (mo/day/yr) 10/6/2008 under the business name of GeoCore, Inc. by (signature) Dan Abolt

OFFICE USE ONLY

T

R

EW

SEC.

1/4

1/4

1/4