


1 LOCATION OF WATER WELL: Fraction SE 1/4 SE 1/4 SE 1/4 Section Number 27 Township Number T 25 8 Range Number R 15 **EW**
 County: WOODSON

Distance and direction from nearest town or city street address of well if located within city?
APPROX 2 M S YATES CENTER KS - HWY 75

2 WATER WELL OWNER: KDOT
 RR#, St. Address, Box #: BOX 366 Board of Agriculture, Division of Water Resources
 City, State, ZIP Code: IDA KS 66749 Application Number: -

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL: *UNKNOWN ft. ELEVATION: 1126.94
 Depth(s) Groundwater Encountered 1. UNKNOWN ft. 2. - ft. 3. - ft.
 WELL'S STATIC WATER LEVEL 13 ft. below land surface measured on mo/day/yr 04-25-89
 Pump test data: Well water was NA ft. after - hours pumping - gpm
 Est. Yield - gpm: Well water was - ft. after - hours pumping - gpm
 Bore Hole Diameter: *6.25 in. to UNKNOWN ft., and - in. to - ft.
 WELL WATER TO BE USED AS: NA 5 Public water supply 8 Air conditioning 11 Injection well
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes - No X; If yes, mo/day/yr sample was submitted -
 Water Well Disinfected? Yes X No -

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued - Clamped -
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded -
 7 Fiberglass GALV. TIN - REMOVED Threaded -
 Blank casing diameter 5 in. to 6 ft., Dia OPEN HOLE in. to - ft., Dia - in. to - ft.
 Casing height above land surface NA in., weight - lbs./ft. Wall thickness or gauge No. -
 TYPE OF SCREEN OR PERFORATION MATERIAL: NA 7 PVC 10 Asbestos-cement
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) -
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE: NA 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes
 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) -
 SCREEN-PERFORATED INTERVALS: From NA ft. to - ft., From - ft. to - ft.
 From - ft. to - ft., From - ft. to - ft.
 GRAVEL PACK INTERVALS: From NA ft. to - ft., From - ft. to - ft.
 From - ft. to - ft., From - ft. to - ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other -
 Grout Intervals: From 4 ft. to 4.5 ft., From 4.5 ft. to 12.5 ft., From - ft. to - ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage *15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage
 Direction from well? UP SLOPE NW How many feet? APPROX 160'-170'

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
6L	10"	TIP SOIL			EL. REF BM 44A
10"	3.5'	CLAY TYPE			LOC. 507 + 24.10
3.5'	4'	CLAY - SAND STONES			85'-4" W & HWY 75
4'	?	LIMESTONE			
		BOTH WELLS - OPEN HOLE			* MEASURED DEPTHS -
		BORE DIAMETER - UNKNOWN - LARGER THAN 6.25"			WELL A 59'-2"
		BOTH WELLS DISINFECTED - BACK FILLED			WELL B 30'
		WITH SAND TO - 12.5' GL			
		COMMUNICATION BETWEEN HOLES			
		CEMENT GROUT - 4.5' - 12.5' GL			
		NEAT CEMENT - 4' to 4.5' GL			* ALL MEASUREMENTS WELL A
					WELL B IS 3' S 4" W
					OF WELL A
		* 15- OIL WELL 165' S - 330' W			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 04-25-89 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 479 This Water Well Record was completed on (mo/day/yr) 04-27-89 under the business name of EBBERTS DRILLING by (signature) Gregan Ebbert

OFFICE USE ONLY
T
R
EW
SEC.
1/4
1/4
1/4