## WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

1. Location of well:	Fraction	Section numb	er Township number	Range number	
2. Distance and direction from nearest town of	WE 1/4 WW 1/4 1/4	wner of well:	7 25	s R 18	(E)/W
Street address of well location if in city:	East 6+ Lola R.R.	or street:	3	eth.	
4 Locate with "X" in section below:	Sketchmap: City,	state, zip code:	Told, King		
N a	the distance of the standard o	Ĺ	6. Bore hole dia.	in. Completion date	12/18
NWNE	Crashand		7. Cable fool Ro	otary Driven Du	9
	The state of the s	andiği		Public supply	
	x well		Irrigation _	Air conditioning 🍂 S	tock
SW non no. Con now SE was no.	X V		9. Casing: Material	Oil field water C	Other
ala andre de la compania del la compania de la compania del la compania de la compania del la com	920000		Threaded Welded RMP PVC_	Surface	in.
5. Type and color of material			Dia in. to 28 ft.	depth!Wall Thickness: ir	lbs./ft.
Photographic angular a		From To	Diain. toft.  10. Screen: Manufacture		
Conduction to the control of the con	5011	0 3	Type W		ons
and California and Ca	Cla Collow	5 15	Slot/gauze 0%	Dia.	
	Hand II		Set between	ft. and	ft.
The state of the s	14.61	15 16	Gravel pack? Siz	e range of materia	3/4_
Small AMTWIR LIN	Jacken) / 4 e	16 35	ft. below land	The state of the s	day/yr.
Julian Ala Mar Mar	ne-2014 Hard	35 50	12. Pumping level below	land surfaces:  hrs. pumping	
AMERICAN CONTROL OF THE PROPERTY OF THE PROPER	Line-Hard	20 8X	ft. after	hrs. pumping	g.p.m.
The State of the Control of the Cont	Shale Sandy	84 112	Estimated maximum yield  13. Water sample submitte		-g.p.m. /day/yr.
Ong graden spall and a spall and a spall and a spall as a spall and a spall and a spall and a spall as a spall	- Hne-Hard	1/2 120	Yes No 14. Well head completion	Date	
Mall Ineressein WTR	Stale - Gran Jank	120 155	Pitless adapter	Inches above	grade
•	dired / line	155 158	15. Well grouted?  With: Neat cement		oncrete
And the control of th	1/12 501	130 191	Depth: From ft.	to <u>(0</u> ft.	
	Lime-Sank	58 100	16. Degrest source of poss ft. Direction	ible contamination.	<u> Îrc</u>
all	Shale-Blue	170 173	Well disinfected upon com	pletion? YesYesYes	No
Actesse in with	11me-Hard	175 25	Manufacturer's name		~
HSGals in Bernarde	Lime SIT	215 234	Length of drop pipe	HP Volt	5
Whe Saltur-5alt	Shale - Black	234 237	Type: Submersible	Turbine	
	second sheet Andedque Hayd	237 238	Jet Centrifugal	Reciproc	
18. Elevation: 19. Remarks:		***************************************	20. Water well contractor'	s certification:	Sec
Topography:			This well was drilled under is true to the best of my kno		eport
Hill			Eureka Well	Service 2	16   51
Slope Upland			Addres225 SWall	nut Eureka	se do.
Valley			Signed Authorized re	presentative	72-18