

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: Allen	NW 1/4 SE 1/4 NE 1/4	2	T 25 S	R 19 EW

Distance and direction from nearest town or city street address of well if located within city?

One Mile South & East of LaHarpe, Kansas

2 WATER WELL OWNER: Allen County Landfill %Director of Public Works	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box # : 1 North Washington	Application Number:
City, State, ZIP Code : Iola, KS 66749	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 3.7 ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 3.7 ft. below land surface measured on mo/day/yr Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter in. to ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well AMW-2S Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	Welded
Blank casing diameter 2 in. to 27 ft., Dia			Threaded X
Casing height above land surface 24 in., weight			lbs./ft. Wall thickness or gauge No. Sch. 40
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC	10 Asbestos-cement	
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify) Factory Slot
SCREEN-PERFORATED INTERVALS:	From 27 ft. to 37 ft.		
GRAVEL PACK INTERVALS:	From 25 ft. to 38 ft.		

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals:	From 0 ft. to 23 ft.	From 23 ft. to 25 ft.		
What is the nearest source of possible contamination:	1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens
	2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage
	3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage
				13 Insecticide storage
				14 Abandoned water well
				15 Oil well/Gas well
				16 Other (specify below)
				N/A
Direction from well?				How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	1.2	Topsoil	38	100	Bentonite Holeplug
1.2	18.5	Iola Limestone			
18.5	20.5	Gr Limestone with Chirt			
20.5	39.5	Chanute Shale			
39.5	39.9	Coal			
39.9	44	Chanute Shale			
44	53.2	Lt Gr Limestone			
53.2	94.7	Chanute Shale			
94.7	100	Gr Silty Limestone			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5/10/94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 458. This Water Well Record was completed on (mo/day/yr) 5-31-94 under the business name of The Winnek Co., Inc. by (signature) [Signature]
