


1 LOCATION OF WATER WELL: Fraction NW Section Number 26 Township Number T 25 S Range Number R 02 E
 County: Sedwick SW 1/4 SW 1/4 SW 1/4

Distance and direction from nearest town or city street address of well if located within city?
3 miles SE of Furley, KS

2 WATER WELL OWNER: NEIS
 RR#, St. Address, Box # : 8808 North 12th Street
 City, State, ZIP Code : Valley Center, KS
 Board of Agriculture, Division of Water Resources
 Application Number: 54.4 54.4

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL 54.4 ft. ELEVATION: 1399.265
 Depth(s) Groundwater Encountered: 1 55.2 ft. 2 ft. 3 ft.
 WELL'S STATIC WATER LEVEL 55.2 ft. below land surface measured on 11/7/2004
 Pump test data: Well water was ft. after hours pumping gpm
 Est. Yield gpm: Well water was ft. after hours pumping gpm
 WELL WATER TO BE USED AS:
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes No ; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
 7 Fiberglass Threaded
 Blank casing diameter 2.5 in. to 44.4 ft. Dia in. to ft. Dia in. to ft.
 Casing height above land surface 2.5 in., weight 0.7 lbs./ft. Wall thickness or gauge No. S&D 40
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless Steel 5 Fiberglass 7 PVC 10 Asbestos-Cement
 2 Brass 4 Galvanized Steel 6 Concrete tile 9 ABS 11 Other (Specify)
 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 0.010 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify) ft.
 SCREEN-PERFORATED INTERVALS: From 30.44.4 ft. to 53.9 ft. From ft. to ft.
 GRAVEL PACK INTERVALS: From 30.5 ft. to 54.5 ft. From ft. to ft.
 From ft. to ft. From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 0 ft. to 30.5 ft., From ft. to ft., From ft. to ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) HAZ waste site
 13 Insecticide storage
 Direction from well? ENE How many feet? 670'

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
<u>0</u>	<u>54.5</u>	<u>Brown plastic to highly plastic clay to weathered clay-shale, with trace to some calcium carbonate nodules</u>			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11/7/2004 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No. 708 This Water Well Record was completed on (mo/day/yr) 12/19/2004 under the business name of AQUATERRA ENVIRONMENTAL SOLUTIONS by (signature) [Signature]