

1 LOCATION OF WATER WELL: County: <u>Sedgwick</u>	Fraction <u>SW 1/4 SW 1/4 SW 1/4</u>	Section Number <u>23</u>	Township Number <u>T 25 S</u>	Range Number <u>R 2 EW</u>
--	---	-----------------------------	----------------------------------	-------------------------------

Distance and direction from nearest town or city street address of well if located within city?

Approx. 3 miles SE of Furlly, KS

2 WATER WELL OWNER: <u>Chemical Waste Management</u>	Board of Agriculture, Division of Water Resources Application Number:
RR#, St. Address, Box # : <u>8806 N 127th St. East</u>	
City, State, ZIP Code : <u>Valley Center, KS 67147</u>	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL <u>16.5</u> ft. ELEVATION: <u>1337.2</u>
	Depth(s) Groundwater Encountered 1 <u>6</u> ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL <u>5.6</u> ft. below land surface measured on mo/day/yr <u>7-18-07</u> Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering <u>11 Injection well</u> 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well 12 Other (Specify below)
	Was a chemical/bacteriological sample submitted to Department? Yes No <u>X</u>; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No <u>(No)</u>

5 TYPE OF BLANK CASING USED: 1 Steel <u>2 PVC</u> 3 RMP (SR) 4 ABS	5 Wrought iron 6 Asbestos-Cement 7 Fiberglass	8 Concrete tile 9 Other (specify below)	CASING JOINTS: Glued Clamped Welded <u>Threaded</u>
Blank casing diameter <u>2</u> in. to <u>8.5</u> ft. Dia in. to ft. Dia in. to ft.	Casing height above land surface <u>23</u> in., weight <u>schd 40</u> lbs./ft. Wall thickness or gauge No.	TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-Cement 2 Brass 4 Galvanized Steel 6 Concrete tile 9 ABS 11 Other (Specify) 12 None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 2 Louvered shutter <u>3 Mill slot</u> 4 Key punched	5 Guazed wrapped 6 Wire wrapped 7 Torch cut	8 Saw cut 9 Drilled holes 10 Other (specify)	11 None (open hole)
SCREEN-PERFORATED INTERVALS: From <u>8.5</u> ft. to <u>16.0</u> ft., From ft. to ft.	GRAVEL PACK INTERVALS: From <u>6.0</u> ft. to <u>16.5</u> ft., From ft. to ft.		

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout <u>3 Bentonite</u> 4 Other	GROUT INTERVALS: From <u>0</u> ft. to <u>6</u> ft., From ft. to ft., From ft. to ft.
What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage <u>16 Other (specify below)</u> <u>Closed Haz Waste facility ~ 2000 ft</u>	Direction from well? How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	1	Topsoil			
1	10	Brown Clay			
10	14	Brown - Gray Clay			
14	16.5	Gray Clay/Shale			
	TD				

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was <u>(1) constructed</u> (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>6-5-07</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No <u>708</u> This Water Well Record was completed on (mo/day/yr) <u>8-9-07</u> under the business name of <u>Aquaterre</u> by (signature) <u>[Signature]</u>
