


BIP-19

1 LOCATION OF WATER WELL: County: <u>Sedgwick</u>	Fraction <u>SW 1/4 SW 1/4 SW 1/4</u>	Section Number <u>23</u>	Township Number T <u>25</u> S	Range Number R <u>2</u> EW
--	---	-----------------------------	----------------------------------	-------------------------------

Distance and direction from nearest town or city street address of well if located within city?

Approx 3 miles SE of Furdy, KS

2 WATER WELL OWNER: <u>Chemical Waste Management</u> RR#, St. Address, Box # : <u>8808 N 127th St. East</u> City, State, ZIP Code : <u>Valley Center, KS 67147</u>	Board of Agriculture, Division of Water Resources Application Number:
--	--

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF COMPLETED WELL <u>16.0</u> <u>bgs</u> ft. ELEVATION: <u>1335.7</u> <u>gs</u> Depth(s) Groundwater Encountered 1 <u>16.0</u> ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL <u>5.48</u> ft. below land surface measured on mo/day/yr <u>7-18-07</u> Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning <u>11 Injection well</u> 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well
	Was a chemical/bacteriological sample submitted to Department? Yes No <u>X</u> ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No <u>No</u>

5 TYPE OF BLANK CASING USED: 1 Steel <u>2 PVC</u> 3 RMP (SR) 4 ABS	5 Wrought iron 6 Asbestos-Cement 7 Fiberglass	8 Concrete tile 9 Other (specify below)	CASING JOINTS: Glued Clamped Welded <u>Threaded</u>
Blank casing diameter <u>2</u> in. to <u>8</u> ft., Dia Casing height above land surface <u>20</u> in., weight <u>schd 40</u> lbs./ft. Wall thickness or gauge No.	TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless Steel 5 Fiberglass <u>7 PVC</u> 10 Asbestos-Cement 2 Brass 4 Galvanized Steel 6 Concrete tile 8 RMP (SR) 11 Other (Specify) 12 None used (open hole)		
SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 2 Louvered shutter <u>3 Mill slot</u> 4 Key punched	5 Guazed wrapped 6 Wire wrapped 7 Torch cut	8 Saw cut 9 Drilled holes 10 Other (specify)	11 None (open hole)
SCREEN-PERFORATED INTERVALS: From <u>8.0</u> ft. to <u>15.5</u> ft., From ft. to ft. GRAVEL PACK INTERVALS: From <u>6.0</u> ft. to <u>16.0</u> ft., From ft. to ft.			

6 GROUT MATERIAL: 1 Neat cement <u>3 Bentonite</u> 4 Other	2 Cement grout
Grout Intervals: From <u>0</u> ft. to <u>6</u> ft., From ft. to ft., From ft. to ft.	
What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage <u>16 Other (specify below)</u> <u>Closed Haz Waste Facility ~ 2000 ft</u>	
Direction from well? How many feet?	

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	1	Fill-clay			
1	2	Topsoil			
2	10	Brown clay			
10	16	Brown-Gray clay Harder near bottom			
		TD			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was <u>(1) constructed</u> , (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>6-6-07</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No <u>708</u> . This Water Well Record was completed on (mo/day/yr) <u>8-9-07</u> under the business name of <u>Aquatera</u> by (signature) <u>[Signature]</u>
--