


1 LOCATION OF WATER WELL: County: <u>Sedgwick</u>	Fraction <u>SW 1/4 SW 1/4 SW 1/4</u>	Section Number <u>23</u>	Township Number T <u>25</u> S	Range Number R <u>2</u> EDW
--	---	-----------------------------	----------------------------------	---------------------------------------

Distance and direction from nearest town or city street address of well if located within city?
Approx. 3 miles SE of Furdy, KS

2 WATER WELL OWNER: Chemical Waste Management
 RR#, St. Address, Box # : 8808 N 127th St East
 City, State, ZIP Code : Valley Center, KS 67147
 Board of Agriculture, Division of Water Resources
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF COMPLETED WELL: <u>18.5</u> ft. ELEVATION: <u>1337.7</u> g Depth(s) Groundwater Encountered 1 <u>9</u> ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL: <u>8.12</u> ft. below land surface measured on mo/day/yr <u>6-27-07</u> Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No <u>X</u> ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No <u>(No)</u>
---	--

5 TYPE OF BLANK CASING USED:
 1 PVC 2 Steel 3 RMP (SR) 4 ABS 5 Wrought iron 6 Asbestos-Cement 7 Fiberglass 8 Concrete tile 9 Other (specify below)
 CASING JOINTS: Glued Clamped
 Welded
 Threaded (PVC)
 Blank casing diameter 2 in. to 10.5 ft., Dia in. to ft., Dia in. to ft.
 Casing height above land surface 19 in., weight Schd 40 lbs./ft. Wall thickness or gauge No.
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 2 Brass 3 Stainless Steel 4 Galvanized Steel 5 Fiberglass 6 Concrete tile 7 RMP (SR) 8 ABS 9 Other (Specify) 10 Asbestos-Cement 11 Other (Specify) 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 2 Louvered shutter 3 Mill slot 4 Key punched 5 Guazed wrapped 6 Wire wrapped 7 Torch cut 8 Saw cut 9 Drilled holes 11 None (open hole) 10 Other (specify) ft.
 SCREEN-PERFORATED INTERVALS: From 10.5 ft. to 18.0 ft., From ft. to ft.
 GRAVEL PACK INTERVALS: From 8.0 ft. to 18.5 ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout intervals: From 0 ft. to 8 ft., From ft. to ft., From ft. to ft.
 What is the nearest source of possible contamination:
 1 Septic tank 2 Sewer lines 3 Watertight sewer lines 4 Lateral lines 5 Cess pool 6 Seepage pit 7 Pit privy 8 Sewage lagoon 9 Feedyard 10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage 14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below)
Closed Haz Waste Facility ~ 2000 ft
 Direction from well? How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
<u>0</u>	<u>1</u>	<u>Topsoil</u>			
<u>1</u>	<u>10</u>	<u>Brown Clay</u>			
<u>10</u>	<u>17</u>	<u>Brown - Gray Clay</u>			
<u>17</u>	<u>18.5</u>	<u>Gray Clay/shale</u>			
	<u>TD</u>				

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6-7-07 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No 708 This Water Well Record was completed on (mo/day/yr) 8-4-07 under the business name of Aquaterna by (signature) [Signature]