


1 LOCATION OF WATER WELL: Fraction SW 1/4 NW 1/4 SW 1/4 Section Number 26 Township Number T 25 S Range Number R 2 E
 County: SEDGWICK

Distance and direction from nearest town or city street address of well if located within city?

3 miles S.E. OF. FURLEY, KS.

2 WATER WELL OWNER: NIES
 RR#, St. Address, Box #: 8808 N. 127th East
 City, State, ZIP Code: VALLEY CENTER, KS. 67147
 Board of Agriculture, Division of Water Resources
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:



4 DEPTH OF COMPLETED WELL: 48.3 ft. ELEVATION: 1393.3

Depth(s) Groundwater Encountered: 1 DRY ft. 2 DRY ft. 3 DRY ft.

WELL'S STATIC WATER LEVEL: DRY ft. below land surface measured on mo/day/yr 3/9/82

NA Pump test data: Well water was DRY ft. after DRY hours pumping DRY gpm

Est. Yield DRY gpm: Well water was DRY ft. after DRY hours pumping DRY gpm

Bore Hole Diameter: 6 in. to 48.3 ft. and DRY in. to DRY ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well

1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well MONITORING WELL

Was a chemical/bacteriological sample submitted to Department? Yes ✓ No ✓; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes ✓ No ✓

5 TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued ✓ Clamped ✓

1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded ✓

2 PVC 4 ABS 7 Fiberglass Threaded ✓

Blank casing diameter 2 in. to 37.3 ft. Dia. 0.70 in. to DRY ft. Dia. DRY in. to DRY ft.

Casing height above land surface 2.5 ft. in. weight 0.70 lbs./ft. Wall thickness or gauge No. SCH. 40

TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement

1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)

2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)

1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes

2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 37.3 ft. to 47.3 ft. From DRY ft. to DRY ft.

From DRY ft. to DRY ft. From DRY ft. to DRY ft.

GRAVEL PACK INTERVALS: From 16.8 ft. to 48.3 ft. From DRY ft. to DRY ft.

From DRY ft. to DRY ft. From DRY ft. to DRY ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 0.0 ft. to 16.8 ft. From DRY ft. to DRY ft.

What is the nearest source of possible contamination: Drum Disposal Trench D-20 10 Livestock pens 14 Abandoned water well

1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well

2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)

3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage HAZ WASTE FACILITY

Direction from well? N/E How many feet? 40 APPROX

FROM TO LITHOLOGIC LOG FROM TO LITHOLOGIC LOG

0.0 48.3 Brown PLASTIC TO HIGHLY PLASTIC 0.0 48.3 CLAY TO WEATHERED CLAY SHALE

(FT.) (FT.) WITH TRACE TO SOME CALCIUM (FT.) (FT.) CARBONATE NODULES

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 2/22/82 and this record is true to the best of my knowledge and belief. Kansas

Water Well Contractor's License No. 416 This Water Well Record was completed on (mo/day/yr) 5/19/82

under the business name of TERRACON CONSULTANTS, Inc. by (signature) [Signature]

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.