

AGES - GARY

WATER WELL RECORD

Form WWC-5

KSA 82a-1212

MW# 7

| | | | | | |
|---|----|--|---|---|---|
| 1 LOCATION OF WATER WELL | | Fraction SW $\frac{1}{4}$ SW $\frac{1}{4}$ SE $\frac{1}{4}$ | Section Number 35 | Township Number T 25 S S | Range Number R 5 E W |
| Distance and direction from nearest town or city street address of well if located within city? | | | | | |
| 2 WATER WELL OWNER: | | DeLons 6th & Main Streets El Dorado, KS 67042 | | | |
| Board of Agriculture, Division of Water Resources Application Number: | | | | | |
| 3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: | | 4 DEPTH OF COMPLETED WELL 24 ft. ELEVATION: Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 18 ft. below land surface measured on mo/day/yr Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter in. to ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No | | | |
| 5 TYPE OF BLANK CASING USED: | | 1 Steel 2 PVC | 3 RMP (SR) 4 ABS | 5 Wrought iron 6 Asbestos-Cement 7 Fiberglass | 8 Concrete tile 9 Other (specify below) 10 Monitoring well |
| CASING JOINTS: Glued Clamped Welded Threaded Blank casing diameter in. to ft., Dia in. to ft., Dia in. to ft. Casing height above land surface F14SH in., weight lbs./ft. Wall thickness or gauge No. | | | | | |
| TYPE OF SCREEN OR PERFORATION MATERIAL: | | | | | |
| 1 Steel 2 Brass | | 3 Stainless steel 4 Galvanized steel | 5 Fiberglass 6 Concrete tile | 7 PVC 8 RMP (SR) 9 ABS | 10 Asbestos-cement 11 Other (specify) 12 None used (open hole) |
| SCREEN OR PERFORATION OPENINGS ARE: | | | | | |
| 1 Continuous slot 2 Louvered shutter | | 3 Mill slot 4 Key punched | 5 Gauzed wrapped 6 Wire wrapped 7 Torch cut | 8 Saw cut 9 Drilled holes 10 Other (specify) | 11 None (open hole) |
| SCREEN-PERFORATED INTERVALS: From 14 ft. to 24 ft., From ft. to ft. From ft. to ft., From ft. to ft., From ft. to ft. - GRAVEL PACK INTERVALS: From 12 ft. to 24 ft., From ft. to ft., From ft. to ft. | | | | | |
| 6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other SAND | | | | | |
| Grout Intervals: From ft. to ft., From ft. to ft., From ft. to ft., From ft. to ft. | | | | | |
| What is the nearest source of possible contamination: | | | | | |
| 1 Septic tank 2 Sewer lines 3 Watertight sewer lines | | 4 Lateral lines 5 Cess pool 6 Seepage pit | 7 Pit privy 8 Sewage lagoon 9 Feedyard | 10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage | 14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below) |
| Direction from well? | | | | | |
| FROM | TO | LITHOLOGIC LOG | | FROM | TO |
| 0 | 3 | Brown Clay | | | |
| 3 | 9 | Black Clay | | | |
| 9 | 24 | Red Brown Clay | | | |
| PLUGGING INTERVALS | | | | | |
| 7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7-15-97 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 607 This Water Well Record was completed on (mo/day/yr) 8-5-97 under the business name of Dennis Environmental Drilling L.L.C. by (signature) <i>Dennis</i> | | | | | |
| INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records. | | | | | |