	· · · · · · · · · · · · · · · · · · ·			******					- 110/10	, Lu	12 13 110.					
LOCATIO	N OF WATER								ection Nun	nber		ip Numbe	er	Range N		
County:			SW								_T 2	25	s .	R 0	5	E
Distance and	direction from	nearest to	own or city st	treet ad	dress of we	ell if loo	cated wit	hin city?								
	335 N. Tope															
2 WATER V	VELL OWNER	₹:			rchant E	ner	gy-Pet	roleui	n Comp	oany	1					
RR#, St. Add	ress, Box #	:	2 N. N	evada	a Ave						Board of	Agricultur	e, Division	of Water	Resou	ırces
	IP Code		Colora	ado S	prings,	<u>CO 8</u>	<u> 80903</u>				Application	n Numbe	er:			
	WELL'S LOCA								40 .		ATION:		1200 2	2 TOC		
AN X IN	SECTION BO	JX:	DEPT	H OF C	OMPLETE	D WE	LL		4.5 π.	ELEV	ATION:		1250.5	2 100	••••	ے
↑		·									2					ft. 🖣
	- Nw	NE	WELL'S	STATIC	WATER L	EVEL			ft. below is	and su	urface measu	ired on m	io/day/yr	`		ft.
	- 1444 T	:		Pump	test data:	We	ll water v	vas		ft.	after	t	nours pump	ping		gpm c
<u>`</u> ₩	1		E Est. Yield	l	apm:	We	ll water v	vas		ft	. after	ł	nours pumi	pina		apm H
-	1 1		Bore Hole	e Diame	eter 8	3 i	in. to		15		ft. and 8 Air cor 9 Dewat		in. to			ft.
	-sw	, -	WELL W	ATER T	O BE USE	DAS:	5 Pul	olic wate	r supply		8 Air cor	nditioning	11 In	jection w	ell	
	- Svv	SE	1 D	omestic	3 Feed	lot	6 Oil	field wat	er supply		9 Dewat	ering	12 0	ther (Spe	cify be	low)
× ×	_		2 In	rigation	4 Indus	strial	7 Lav	vn and g	arden (dor	nestic) 10 Moni	toring we		.		
	S										Yes N					was
			submitted								ter Well Disin					
5 TYPE OF	BLANK CAS	ING USED			5 Wrou	Jaht Ir	on	8 Cor			CASING					
	el				6 Acho	etoe-C	Cement	g Oth	er (specify	belov	w)	30	Waldad			
2 PVC		4 ABS						9	, , ,		,		Welded Threaded	r	luch	
		4 ABS		4.0	7 Fiber	rgiass 							Inreaded		lusii	البيد
Blank casing	diameter nt above land : CREEN OR PI		in. to	4.8	ft., l	Dia			n. to		ft., Dia		in.	to		^{ft.}
Casing heigh	nt above land	surface	36		in., weight		0	703		s./ft.	Wall thickne	ss or gau	ge No.	Sci	h. 40	
TYPE OF SC	CREEN OR PI	ERFORAT	ION MATER	IAL:					7 PVC	<i>)</i>	10 11 12	Asbesto	s-cement			
1 Stee	el	3 Stai	nless steel		5 Fiber	rglass			8 RMP (SR)	11	Other (s	pecify)			
2 Bras			vanized stee		6 Cond				9 ABS		12	None us	ed (open h	iole)		
	R PERFORAT										8 Saw cu	t 	11	None (o	pen ho)le)
	tinuous slot vered shutter		4 Key punc				Wire w				9 Drilled I	noies				
									Δ.	<u> </u>	10 Other (specify)			;	
SCREEN-PE	ERFORATED	INTERVAL									rom					
			From			ft. to	·			ft. F	rom		ft. to			ft. ;
GRA	AVEL PACK IN	NTERVALS	S: From		3	ft. to	·	15		∴ft. F	rom		ft. to			ft.
			From			ft. to)			ft. F	rom		ft. to			ft.
6 GROUT	MATERIAL:	1 Ne	at cement	2	Cement g	rout		3 I	Bentonite	\supset	4 Other					
 Grout Interva	als From	0	ft. to	3	ft. Fro	om			ft. to		ft. Fr	om		ft. to		ft.
	nearest source					-					tock pens		14 Aband			
	otic tank	p				7 F	Pit privv				storage		15 Oil we			
	ver lines		5 Cess				Sewage i				izer storage		16 Other			
	tertight sewer	lines		•			eedyard				ticide storage		10 00101	(opcony a	,0.011,	
Direction fro	•.		o ocep	age pit		5 1	Jouyard	•			feet?	-				
FROM	TO	CODE		LITHO	LOGIC LO	G		FRO			ieer:	PLUG	GING INTE	-RVALS		
0	5		Clayey Si			-		1				. 200	J 10 1141E			
5	8.5		Silty Clay					 								
8.5	15		Limeston			-		1								
	7.0															
								1								
								-								
,												7,00				
								1				·				
	1															
7 CONTRA	ACTOR'S OR	LANDOW	NER'S CER	TIFICAT	TION: This	water	well was	(1) cons	structed 2) reco	nstructed, or	(3) pluga	ed under m	ny jurisdic	tion and	d was
	on (mo/day/yr)				0-05					-	true to the be					
	Contractor's L				531						ecord was c	-	_			
							•				COOLU WAS C				.:	
	usiness name				al Servi				oy (signatu	ire)			on M.		407	0.014
INSTR	UCTIONS: PI	ease fill in b	lanks and circ	te the co	orrect answe	rs. Se	nd three	copies to	Kansas De	partme	ent of Health a	nd Enviror	nment, Bure	au of Wat	er, 1000	JSW