GSI Job No	. 05/094			\^/ATED \^/	/ELL DEO	000 E	\A04/C E	VCA 00- 4	O10 ID No			OW-29
1 LOCATIO	N OF WATER	R WELL:	Fraction		ELL REC	ORD FO	orm WWC-5 Section	KSA 82a-1			Range Nu	mber
County:	_		SW		SW 5	4 SW		26	T 25			/ Y
Distance and	direction from		town or city str				within city?	,				
			Dorado (For				atroleum (20.000				
_	VELL OWNE					iergy-P	etroleum (ompan				
	ress, Box #		2 N. Ne			O 0000	2				ision of Water R	lesources
	IP Code WELL'S LOC			do Spri	ngs, c	0 8090	<u>. </u>		Application	Number:		
	SECTION B		" 4 DEPTH	OF COM	PLETED	WELL	19	ft. ELE\	/ATION:	129	4.68 TOC	
<u> </u>	- i-								. 2			
	į		WELL'S S	TATIC WA	TER LE	/EL	ft. b	elow land s	urface measure	d on mo/day	/yr	
	-NW	- NE							t. after			
₩ w		!	Est. Yield		gpm:	Well wate	r was	f	t. after	hours i	oumpina	apm
Ť " –			Bore Hole	Diameter	8	in. to	19.	5	ft. and 8 Air condit 9 Dewaterii	ir	n. to	ft.
	-sw	- SF	WELL WA	TER TO B	E USED	AS: 5 F	ublic water su	pply	8 Air condit	ioning 1	1 Injection well	
l x	i	i		mestic 3	3 Feed lo	ot 6 C	Dil field water s	upply	9 Dewaterin	<u>19</u> 1	2 Other (Specif	fy below)
† <u> </u>		_!	1 '	gation 4	1 Industri	ial 7 L	awn and garde	en (domesti	c) 10 Monitori	ng well		
	s			mical/bact	teriologica	al sample	submitted to D		Yes No			
<u> </u>			submitted						ter Well Disinfed			
	BLANK CAS			5	Wrough	nt Iron	8 Concre	te tile specify belo	CASING JO			
1 Ste			1P (SR)				t 9 Other (Wek	ded	-
2 PVC		4 AE	S	7	Fibergl	ass	•			Threa	aded FI	usn
Blank casing	diameter	-	in. to	9	ft., Dia	a	in. to		ft., Dia		_ in. to	ft.
Casing heigh	nt above land	surface	36	in.,	weight .		0.703	bs./ft.	Wall thickness of 10 As	or gauge No	Scn.	40
1 Stee		2 St	IION MATERIA	\L: 5	Eiboral	200	\sim	PVC PMD (SD)	10 As 11 Ot	bestos-cem	ent	
2 Bras		4 Ga	Ivanized steel	6	Concre	te tile	9	ABS	11 Ot 12 No 8 Saw cut 9 Drilled hole	ne used (on	en hole)	
		TION OPE	NINGS ARE:		00,10,10	5 Gau	zed wrapped		8 Saw cut	,,,o aboa (op	11 None (ope	en hole)
l	tinuous slot	(3 Mill slot)		6 Wire	wrapped		9 Drilled hole	es		
2 Lou	vered shutter		4 Key punch	ed		7 Torc	h cut		10 Other (sp	ecify)		
SCREEN-PE	RFORATED	INTERVA	LS: From	9		ft. to	19	ft. F	From	ft.	to'	ft.
			From	<u></u>		ft. to		ft. I	From	ft.	to	ft.
GR/	VEL PACK I	NTERVAL	S: From	7.4	4	ft. to	19.5	ft. I	From	ft.	to	ft.
			From			ft. to		ft.	From	ft.	to	ft.
6 GROUT	MATERIAL:	1 N	eat cement	_ 2 Ce	ement gro	ut	3 Bent	tonite	4 Other			
Grout Interva	als From	<u>U</u>	ft. to	1.4	ft. From		ft. t	0	ft. From		ft. to	ft.
		e of possi	ble contaminati						stock pens	14 At	pandoned water	well
	otic tank		4 Latera						storage	15 O	il well/ Gas well	
	ver ines tertight sewer			5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below) 6 Seepage pit 9 Feedyard 13 Insecticide storage							ow)	
Direction fro	-	illies	о Зеера	ge pit	•	o reeuya	iid	How many	•			
FROM	TO	CODE	ı	ITHOLOG	IC LOG		FROM	TO		LUGGING I	NTERVALS	
0	12.5	CL	Silty Clay									
12.5	15	VG	Clayey, gr		sand							
15	19.5		Limestone	<u> </u>								
		 										
		 										
-		-						-				
7 CONTR	ACTOR'S OF	LANDOV	I VNER'S CERTI	FICATION	l This w	ater well w	res (1) construe	ted (2) reco	onstructed, or (3)	plugged und	ler my jurisdiction	n and was
									true to the best			
			o		531				Record was com			
											N. Irwin	
	usiness name		Geotec					signature)	ent of Health and I			1000 \$ \4/
Jackso	on St., Ste. 420	, Topeka, Ł	Cansas 66612-13	67. Teleph	none: 913	-296-5545.	Send one to W	ATER WELL	OWNER and retain	in one for you	ir records.	1000 5 44