SI Job No. 057094	MATER	WELL BEOOK	DD 5	10MO E	KCA 00-	1010 ID No		OW-24
LI CONTION OF WATER WELL.		WELL RECO	KU Form v		n Numbe	a-1212 ID No		Range Number
LOCATION OF WATER WELL:	Fraction 5W 1/2	SW .	ew.		26	er Township T 25		~~ / Y
county: Butler Distance and direction from nearest town					20	1 23	S	R 05 E
1835 N. Topeka, El Dor				i Oity :				
WATER WELL OWNER:	El Paso Mero			oleum C	ompa	inv		
RR#, St. Address, Box # :	2 N. Nevada		. 57		,	•	ricultura Divis	sion of Water Resources
	Colorado Sp		20003					Sion of Water Resources
City, State, ZIP Code : LOCATON WITH						Application		
AN "X" IN SECTION BOX:	DEPTH OF CO	MPLETED W	/ELL	22	ft. EL	EVATION:	1304	1.85 TOC
	Depth(s) Groundw	ater Encount	ered 1	16		ft. 2	ft.	3ft.
[WELL'S STATIC V	WATERIEVE	1	ft h	elow land	d surface measure	d on mo/day/v	ır
NWNE	Pump	test data: \A	lell water was		0.011 10.10	ft after	hours n	umping gpm
₩ W	Est. field	gpm: v	veli water wa:	s <u></u>		. It. aiter	nours p	
ī I ! I ! I !	Bore Hole Diamete					ft. and 8 Air condi	in tioning 11	to ft.
SW SE	1 Domestic	3 Feed lot	5. 5 Public 6 Oil fie	ld water su	upolv	9 Dewateri	ing 12	Injection well Other (Specify below)
	2 Irrigation	4 Industrial	7 Lawn	and garde	n (dome	estic) 10 Monitor	ing well	,
S								mo/day/yr sample was
	submitted		Junipio addit			Water Well Disinfe		V
TYPE OF BLANK CASING USED:		5 Wrought	Iron G	R Conse				
	CD)	6 Asbestos	11011 C	Other /	specify h	elow)		d Clamped
1 Steel 3 RMP (5K)			9 0 1101 (speeny be	J.511)		ed Hush
2 PVC 4 ABS	_	7 Fiberglas						
Blank casing diameter 2	in. to 7	ft., Dia		in. to		ft., Dia		in. toft.
Casing height above land surface	36 i	n., weight	0.7	03	lbs./	/ft. Wall thickness	or gauge No.	Sch. 40
TYPE OF SCREEN OR PERFORATION	N MATERIAL:			(7 I	ツロノ	10 A	sbestos-ceme	ent
1 Steel 3 Stainle	ess steel	5 Fiberglas	SS	8 . F	RMP (SR	₹) 11 0	ther (specify)	
	nized steel				ABS	12 N	one used (ope	en hole)
SCREEN OR PERFORATION OPENIN	Mill slot		5 Gauzed v			8 Saw cut	laa	11 None (open hole)
1 Continuous slot 3 2 Louvered shutter 4	Key punched		6 Wire wrap 7 Torch cut			9 Drilled hol		
	Teem	7 4	*-	22	4	To Outer (Sp		
SCREEN-PERFORATED INTERVALS:	- From	π.	10			t. From		toft.
	From	π.	to		11	t From	π. ι	toft.
GRAVEL PACK INTERVALS:								toft.
	From	ft.	to		f	t. From	ft. 1	to ft.
6 GROUT MATERIAL: 1 Neat of	cement 2	Cement grou	t	3 Bent	onite	→ 4 Other		to ft.
Grout Intervals From 0	ft. to 4.7	ft. From		ft. to		ft. From	n	ft. toft.
What is the nearest source of possible of	contamination:				10 Liv	vestock pens	14 Ab	andoned water well
1 Septic tank	4 Lateral lines	7	Pit privy		11 Fu	uel storage	15 Oil	well/ Gas well
2 Sewer lines	5 Cess pool	8	Sewage lag	joon	12 Fe	ertilizer storage	16 Ot	her (specify below)
3 Watertight sewer lines	6 Seepage pit	9	Feedyard		13 In	secticide storage		
Direction from well?						any feet?		
FROM TO CODE		OGIC LOG		FROM	TO		PLUGGING I	NTERVALS
	Ity Clay							
	and							
	ay	····						
19 23 Li	mestone				-			
	·				-			
					-			
					-			
						-		
					\bot			
7 CONTRACTOR'S OR LANDOWNE	R'S CERTIFICATI	ON: This wat	er well was (1) construc	ted (2) n	reconstructed, or (3) plugged und	er my jurisdiction and was
completed on (mo/day/yr)								edge and belief. Kansas
Water Well Contractor's License No.						ell Record was con	•	
							Allison N	
under the business name of INSTRUCTIONS: Please fill in blan	Geotechnica				signature			
Jackson St., Ste. 420, Topeka, Kans								