


1 LOCATION OF WATER WELL:		Fraction County: Butler SW $\frac{1}{4}$ NE $\frac{1}{4}$ SE $\frac{1}{4}$	Section Number 27	Township Number T 25 S	Range Number R 05 E
Distance and direction from nearest town or city street address of well if located within city? 1835 N. Topeka, El Dorado (Former Coastal Refinery)					
2 WATER WELL OWNER:		El Paso Merchant Energy-Petroleum Company 2 N. Nevada Ave Colorado Springs, CO 80903		Board of Agriculture, Division of Water Resources Application Number:	
3 LOCATE WELL'S LOCATON WITH AN "X" IN SECTION BOX:					
		4 DEPTH OF COMPLETED WELL Depth(s) Groundwater Encountered	26 ft. ELEVATION: 1324.08 TOC		
		WELL'S STATIC WATER LEVEL Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was	ft. after	hours pumping	gpm
		Bore Hole Diameter 8 in. to 26.3 ft. and in. to ft.			
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well			
		1 Domestic 3 Feed lot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		2 Irrigation 4 Industrial 7 Lawn and garden (domestic) 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes <input checked="" type="checkbox"/> No <input type="checkbox"/> If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes <input type="checkbox"/> No <input checked="" type="checkbox"/>			
5 TYPE OF BLANK CASING USED:		5 Wrought Iron 6 Asbestos-Cement 7 Fiberglass	8 Concrete tile 9 Other (specify below)	CASING JOINTS: Glued <input type="checkbox"/> Clamped <input type="checkbox"/> Welded <input type="checkbox"/> Threaded <input checked="" type="checkbox"/> Flush	
1 Steel 2 PVC		3 RMP (SR) 4 ABS			
Blank casing diameter 2 in. to 16		ft. Dia	in. to	ft. Dia	in. to ft.
Casing height above land surface 36		in., weight 0.703	lbs./ft.	Wall thickness or gauge No. Sch. 40	
6 TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 2 Brass		3 Stainless steel 4 Galvanized steel	5 Fiberglass 6 Concrete tile	7 PVC 8 RMP (SR) 9 ABS	10 Asbestos-cement 11 Other (specify) 12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 2 Louvered shutter 3 Mill slot 4 Key punched					
5 Gauzed wrapped 6 Wire wrapped 7 Torch cut		8 Saw cut 9 Drilled holes 10 Other (specify)			
SCREEN-PERFORATED INTERVALS: From 16 ft. to 26		ft. From	ft. to		
From		ft. From	ft. to		
GRAVEL PACK INTERVALS: From 13.8 ft. to 26.3		ft. From	ft. to		
From		ft. From	ft. to		
6 GROUT MATERIAL: 1 Neat cement Grout Intervals From 0 ft. to 13.8 ft. From		2 Cement grout 3 Bentonite	4 Other		
		ft. to	ft. From		
What is the nearest source of possible contamination: 1 Septic tank 2 Sewer lines 3 Watertight sewer lines 4 Lateral lines 5 Cess pool 6 Seepage pit 7 Pit privy 8 Sewage lagoon 9 Feedyard 10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage 14 Abandoned water well 15 Oil well/ Gas well 16 Other (specify below)					
Direction from well?					
FROM 0 TO 8.5 CODE CL		LITHOLOGIC LOG Silty Clay Limestone		PLUGGING INTERVALS	
8.5 26.3					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/yr) 5-10-05 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 531 This Water Well Record was completed on (mo/day/yr) 7-20-05					
under the business name of Geotechnical Services, Inc. by (signature) Allison M. Irwin					
INSTRUCTIONS: Please fill in blanks and circle the correct answers. Send three copies to Kansas Department of Health and Environment, Bureau of Water, 1000 S W Jackson St, Ste. 420, Topeka, Kansas 66612-1367. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					