an oc	TON OF W	ATT OUT OF THE		TER WELL RECO	RD Form V	WC-5 KS/				
	Butler	ATER WELL:	Fraction SW 2	V CTC 1/	CNV 1/	Section Nur		hip Number	Range Number	
		on from pooroot to			SW 1/4	35	T	25 S	R 5 (E)W	
Distance and direction from nearest town or city street address of well if located within city? 700 North Starr, El Dorado, Kansas										
•										
[2] WA	IER WELL C	WNER: Wester	n Resources,	Inc.						
		ox# : P.O. Bo						_	ision of Water Resources	
	City, State, ZIP Code : Topeka, Kansas 66601							Application Number:		
3 LOCATE WELL'S LOCATION 4 DEPTH OF COMPLETED WELL										
N   Depth(s) Groundwater Encountered 1ft. 2ft. 3										
<b>I</b>									yr 2/25/98	
	l w	NE	Pur	np test data: We	ll water was .	NA	ft. after	hours pu	mping gpm	
	. 1464	NE	Est. Yield N	NAgpm: We	ell water was .	. <i></i>	ft. after	hours pu	mping gpm	
Wile Wile		_	Bore Hole Diar	meter 1	in. to	.20	.ft., and	ir	n. to ft.	
- vv		E WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well								
1	l		1 Domesti	c 3 Feedlot	6 Oil field	water supply	9 Dewaterin	ng 12	Other (Specify below)	
	sw	SE	2 Irrigation	n 4 Industria	l 7 Lawn a	nd garden on	ly (10) Monitorin	gwell		
↓	l x			al/bacteriological	sample submit	ted to Depart			, mo/day/yr sample was	
<u>*</u>		<del></del>	submitted				Water Well Disi	nfected? Yes	No <b>√</b>	
5 TYPE	OF BLANK	CASING USED:		5 Wrought iron	n 8 C	oncrete tile	CASIN	3 JOINTS: Glue	d Clamped	
1	Steel	3 RMP (SI	₹)	6 Asbestos-Ce	ement 9 0	Other (specify	below)	Wek	ded	
(2)	PVC	4 ABS		7 Fiberglass				Thre	aded. 🗸	
Blank ca	sing diamete	r	. in. to	10 ft, Dia		in. to	ft., Dia	1	. in. to ft.	
Casing h	eight above	land surface	29.52	. in., weight	Sch 4	0	lbs./ft. Wall thick	ness or gauge I	No	
TYPE O	F SCREEN C	R PERFORATION	N MATERIAL		G (7	PVC	10	Asbestos-cem	ent	
1	Steel	3 Stainless	s steel	5 Fiberglass	V	RMP (SR)	11	Other (specify	)	
2	Brass	4 Galvaniz	ed steel	6 Concrete tile		ABS		None used (or		
SCREEN	OR PERFO	RATION OPENIN	GS ARE:	5	Gauzed wrapp	ed	8 Saw cut	, ,	11 None (open hole)	
1	Continuous s	slot (3)M	fill slot		Wire wrapped		9 Drilled ho	oles	(-)	
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)										
SCREEN-PERFORATED INTERVALS: From 10 ft. to										
From										
	GRAVEL PA	CK INTERVALS:	From	8ft	to	0 ft.,	, From	ft.	to ft	
			From	ft.	to	ft.,	, From	ft.	to ft	
6 GRO	JT MATERIA	L: 1 Neat	cement	2 Cement grout	(3)E	Bentonite	4 Other			
Grout Intervals: From										
		ource of possible					Livestock pens		bandoned water well	
	ptic tank	4 Later					11 Fuel storage 15 Oil well/Gas well			
	wer lines	5 Cess					12 Fertilizer storage (16) Other (specify below)			
3 W	atertight sewe		page pit 9 Feedyard				13 Insecticide storage Former Tank Basin			
	from well?	West	<b>5</b> (				many feet? 60		or aron 1 days Dubin.	
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS										
0	1	Gravel,								
1	12	Clay, Red Bro	own							
12	20	Clay, Brown								
-						-				
								*****		
					<del></del>		MW2 . Tag # 0	0264620 Abov	egrade	
							MW2, Tag # 00264620, Abovegrade Project Name: El Dorado Service Center			
							GeoCore # 569, KDHE # U2 008 1328			
7 00	DACTORS C		CEPTIFICAT	TONI. This waster	unil uno (1)	notruoted (0)				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year)										
					This 184-4:					
				527				(morday/yr)		
	business na			re Services, In			ignature)	~ Kold		
INST	RUCTIONS: Us	e typewriter or ball poi	nt pen. PLEASE P	RESS FIRMLY and PI	RINT clearly. Plea	ase fill in blanks,	underline or circle the	correct answers. S	end top three copies to Kansas	