



1 LOCATION OF WATER WELL: County: Butler		Fraction SW 1/4 SW 1/4 SW 1/4	Section Number 26	Township Number T 25 S	Range Number R 5 E
Distance and direction from nearest town or city street address of well if located within city? 1802 N. Star – El Dorado					
2 WATER WELL OWNER: Union Tank Car Company RR#, St. Address, Box # : 175 W. Jackson City, State, ZIP Code : Chicago, IL 60604		Board of Agriculture, Division of Water Resources Application Number: _____			
3 LOCATE WELL'S LOCATON WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL 26.5 ft. ELEVATION: Depth(s) Groundwater Encountered 1 Dry ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 8 in. to 26.5 ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feed lot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden (domestic) 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No X			
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 2 PVC 4 ABS		5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued _____ Clamped _____ 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded Flush			
Blank casing diameter 2 in. to 16.5 ft., Dia in. to ft., Dia in. to ft.					
Casing height above land surface 36 in., weight 0.703 lbs./ft. Wall thickness or gauge No. SCH. 40					
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) 7 PVC 10 Asbestos-cement					
SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From 16.5 ft. to 26.5 ft. From ft. to ft. From ft. to ft.					
GRAVEL PACK INTERVALS: From 14.5 ft. to 26.5 ft. From ft. to ft. From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals (10" casing) From 1 ft. to 14.5 ft. From ft. to ft. From ft. to ft. From ft. to ft.					
What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/ Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)					
Direction from well? How many feet?					
FROM 0	TO 26.5	CODE Clay	LITHOLOGIC LOG		
FROM 26.5	TO	CODE Limestone	PLUGGING INTERVALS		
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed , (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/yr) 03/25/10 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 531 This Water Well Record was completed on (mo/day/yr) 04/28/10 under the business name of Geotechnical Services Inc. by (signature) 					
INSTRUCTIONS: Please fill in blanks and circle the correct answers. Send three copies to Kansas Department of Health and Environment, Bureau of Water, 1000 S W Jackson St., Ste. 420, Topeka, Kansas 66612-1367. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					

OFFICE USE ONLY

SEC