WATER WELL REC	JORD	Form WV	VC-5	Division	n of Water	Resources App. No	0,	
1 LOCATION OF WA County: Butler	TER WELL:	Fraction 1/4 SW 1/4 SW	1/4 SW 1/4	Section N		Township No.	Range Number R 5 XIE □W	
	f unknown, distance &	Global Positioning System (GPS) information:						
	owner's address, check	Latitude: .37. 8400 (in decimal degrees) Longitude: 96. 85904 (in decimal degrees) Elevation:						
Former El Paso Refinery; N. Topeka St. & W. Refinery Rd.					Longitude: 96. 15904 (in decimal degrees)			
El Dorado, KS					Elevation:			
2 WATER WELL OWNER: El Paso Corporation					Datum: ☐ WGS 84, ☑ NAD 83, ☐ NAD 27 Collection Method:			
RR#, Street Address, Box #: 2 North Nevada				GPS unit (Make/Model: Garmin 60				
City, State, ZIP Code : Colorado Springs, CO 80903				☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey				
يسميد مساعلتان والمقارع والمساورة وا	Joioraa			Est. Accura	acy: 🔲 <	3 m, 🖊 3-5 m, 🗌	5-15 m, $\square > 15$ m	
3 LOCATE WELL	4 DEPTH OF	COMOT BURNEY		9	Δ			
WITH AN "X" IN SECTION BOX:								
N	WELL'S STATIC WATER LEVEL							
	Pump test data: Well water was							
EST. YIELDgpm. Well water wasft. afterhours pumping								
W E Bore Hole Diameter . 2. 2. in. toft., andin. toft.							.ft.	
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well								
SW SE Domestic								
☐ Irrigation ☐ Industrial ☐ Domestic-lawn & garden ☑ Monitoring well								
Was a chemical/bacteriological sample submitted to Department? ☐ Yes ☑ No If yes, mo/day/yr sample was submitted								
Water well disinfected? Yes No								
5 TYPE OF CASING USED: Steel PVC Other								
CASING JOINTS: Glued Clamped Welded Threaded								
Casing diameter .1 in. to								
Casing height above land surface. 30 in., Weight								
TYPE OF SCREEN OR PERFORATION MATERIAL:								
☐ Steel ☐ Stainless Steel ☐ PVC ☐ Other (Specify)								
Brass Galvanized Steel None used (open hole)								
SCREEN OR PERFORATION OPENINGS ARE: Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)								
Louvered shutter Key punched Wire wrapped Saw cut, Other (specify)								
Louvered shutter Key punched Wire wrapped Saw cut Other (specify) SCREEN-PERFORATED INTERVALS: From ft., from ft., From ft., From ft.								
From								
GRAVEL PACK INTERVALS: From								
From ft. to ft., From ft. to ft.								
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other								
Grout Intervals: From								
Septic tank								
Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water well								
☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well Former Oil Refinery Direction from well Distance from well								
Direction from well							The state of the s	
FROM TO Silv	LITHOLOG	IIC LOG	FROM	TO L	ATHO. LO	og (cont.) or PLI	JGGING INTERVALS	
5 19 51	1 1					·		
	mestone							
	11,0,10,10							
						- white and the second		
	***************************************	yen and and and and						
					· · ·			
7 CONTRA CHORSE O	D.T. AND ON AND	NO CEDITITIO ATTA	Y. ODL		<u> </u>	; 1		
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was a constructed, reconstructed, or plugged under my jurisdiction and was completed on (mo/day/year) 11 22								
Kansas Water Well Contractor's License No								
under the business name of Selow Ground Sur Rac. Inc. by (signature)								
INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks and check the correct answers. Send three copies (white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.								
Telephone 785-296-5522. Send one copy to WATER WELL OWNER and retain one for your records. Include <u>fee</u> of \$5.00 for each <u>constructed</u> well. Visit us at http://www.kdheks.gov/waterwell/index.html .								
KSA 82a-1212 Check: White Copy, Blue Copy, Pink Copy								

5B08