County: Butler	1/4 NE 1/4 SE 1/4 SI	1/4 34	25 S 5 ☑ E		
Street/Rural Address of Well Location; if unknown, distance and direction from nearest town or intersection. If at owner's address, check here 230' SW of 8th Ave & Topeka St, El Dorado		Global Positioning Systems (GPS) Information: Latitude: (in decimal degrees) Longtitude: (in decimal degrees) Elevation: Datum: WGS84 NAD83 NAD27			
	AL Petrochemical Refining Thomas Jones Wy, Ste 150 PA 19341	Collection Method: GPS unit Make/Model: Digital Map/Photo Topographic Map Land Surv Est. Accuracy: < 3 m 3-5 m 5-15 > 15			
MARK WELL'S LOCATION WITH AN "X" IN SECTION BOX: N NE NE SW SE X	WELL'S STATIC WATER WELL WAS USED AS: Domestic Public Irrigation Old Fi Feedlot Domes	Water Supply eld Water Supply stic (Lawn/Garden) inditioning	 □ Dewatering □ Monitoring □ Injection Well ✓ Other Observation well 		
TYPE OF BLANK CASING USED: ☐ Steel ☐ RMP (SR) ✓ PVC ☐ ABS Blank casing diameter: 4 Cooling bright above on below land away.	☐ Wrought ☐ I ☐ Asbestos/Cement ☐ C in. Was casing pulled?	Concrete Tile	Other: To 3' bgs		
Casing height above or below land sur GROUT PLUG MATERIAL:	Moat cement ☐ Cemen	t grout	nite Other:		
Grout Plug Intervals: From 3	ft. To 130 ft. From _	ft. To			
□ Sewer lines □ Pit □ Watertight sewer lines □ Se □ Lateral lines □ Fe	epage pit	storage e storage d water well	Other (specify below): Unknown rection from well: ow many feet:		
ROM TO PLUG	GING MATERIAL FR	ом то	PLUGGING MATERIAL		
0 3 Native soil					
3 130 Neat ceme	ent (4")		W-15D (Was Pester Corr		

Def 18

INSTRUCTIONS: Use typewriter or ballpoint pen. Please press firmly and print clearly. Please fill in blanks, underline or circle the correct answers. Send one copy to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Ste. 420, Topeka, Kansas 66612-1367. Telephone 785/296-5524. Send one to Water Well Owner and retain one for your records. Visit us at http://www.kdheks.gov/waterwell/index.html.

1 LOCATION OF WATER WELL: County: Butler	WATER		m WWC-5	KSA 82a-		
County. DULLET	Fraction NE 1/4	SE ¼ SE		ion Number 34	Township Num	
Distance and direction from neares			1/4	34	т 25	—s R 5 (€) W
1/8 mile N. of El					(W-15)	(15D)
2 WATER WELL OWNER: Pes	ter Corporation	n		, , , , , , , , , , , , , , , , , , , ,		
RR#, St. Address, Box # : P.	0. Box 10006				Board of Agri	culture, Division of Water Resource
City, State, ZIP Code : Des	Moines, IA 5	0306			Application N	
LOCATE WELL'S LOCATION W						GL
AN "X" IN SECTION BOX:						ft. 3
 						_{o/day/yr} 12-20-86
NW NE						nours pumping gpm
	Est. Yield	gpm: Well water w	as	ft. aff	er	nours pumping gpm
W I I	E Sore Hole Diamet	97		F. 3.5. P. C	De realization	in. to 2/ft
	1 1 Domontio	3 Feedlot 6 (Til field water	supply (Dewatering	12 Other (Specify below)
sw se	2 Irrigation					
^	Was a chemical/ba					; If yes, mo/day/yr sample was sul
I s	mitted				er Well Disinfected?	
5 TYPE OF BLANK CASING USE	:D:	5 Wrought iron	8 Concre	te tile	CASING JOINT	S: Glued ClampedXX
	P (SR)	6 Asbestos-Cement	9 Other (specify below)	Welded
PVC 4 ABS		7 Fiberglass				Threaded
Blank casing diameter 4						
Casing height above land surface.		n., weight 2001	_		. Wall thickness or	gauge No
TYPE OF SCREEN OR PERFORA			P PVC	-		tos-cement
		5 Fiberglass		P (SR)		(specify)
2 Brass 4 Galv SCREEN OR PERFORATION OPE		6 Concrete tile	9 ABS	-	_	used (open hole)
	3 Mill slot	5 Gauzed v 6 Wire wra			Saw cut Drilled holes	11 None (open hole)
	4 Key punched	7 Torch cu	• •			
SCREEN-PERFORATED INTERVA			_			ft. to
						ft. to
GRAVEL PACK INTERVA						ft. toft
	From	ft. to		ft., From		ft. to ft
-	T.	Cement grout				
Grout Intervals: From. 0.0		5 ft., From	ft. t			
What is the nearest source of poss		7.5%		10 Livest	•	14 Abandoned water well
	Lateral lines	7 Pit privy		11 Fuel s	_	15 Oil well/Gas well
2 Sewer lines 5 0 3 Watertight sewer lines 6 5	Cess pool	8 Sewage lagoon 9 Feedyard			er storage	16 Other (specify below)
Direction from well? West	эевраде рк	5 reeuyaru		How man		Fuel tank
FROM TO	LITHOLOGIC L	OG	FROM			7101001010
	develor manage			TO	LI	HULUGIC LOG
0.01 2.01 Clay	gark grav			10	U	THOLOGIC LOG
0.0 2.0 Clay, 2.0 4.75 Clay,	dark gray brown			10		HOLOGIC LOG
0.0 2.0 Clay, 2.0 4.75 Clay, 4.75 5.00 Clay,	brown			10	L	HOLOGIC LOG
2.0 4.75 Clay, 4.75 5.00 Clay, 5.0 8.5 Limest	brown tan one weathered			10		HOLOGIC LOG
2.0 4.75 Clay, 4.75 5.00 Clay, 5.0 8.5 Limest 8.5 20.5 Shale,	brown tan one weathered yellow/brown					HOLOGIC LOG
2.0 4.75 Clay, 4.75 5.00 Clay, 5.0 8.5 Limest 8.5 20.5 Shale, 20.5 21.0 Shale,	brown tan one weathered yellow/brown gray/brown					HOLOGIC LOG
2.0 4.75 Clay, 4.75 5.00 Clay, 5.0 8.5 Limest 8.5 20.5 Shale, 20.5 21.0 Shale, 21.0 24.5 Shale,	brown tan one weathered yellow/brown gray/brown dark gray					HOLOGIC LOG
2.0 4.75 Clay, 4.75 5.00 Clay, 5.0 8.5 Limest 8.5 20.5 Shale, 20.5 21.0 Shale, 21.0 24.5 Shale, 24.5 34.0 Soft z	brown tan one weathered yellow/brown gray/brown dark gray ones					HOLOGIC LOG
2.0 4.75 Clay, 4.75 5.00 Clay, 5.0 8.5 Limest 8.5 20.5 Shale, 20.5 21.0 Shale, 21.0 24.5 Shale, 24.5 34.0 Soft z 34.0 90.5 Limest	brown tan one weathered yellow/brown gray/brown dark gray ones one, gray frac	tured				HOLOGIC LOG
2.0 4.75 Clay, 4.75 5.00 Clay, 5.0 8.5 Limest 8.5 20.5 Shale, 20.5 21.0 Shale, 21.0 24.5 Shale, 24.5 34.0 Soft z 34.0 90.5 Limest 90.5 126.0 Chert	brown tan one weathered yellow/brown gray/brown dark gray ones one, gray frac	tured				HOLOGIC LOG
2.0 4.75 Clay, 4.75 5.00 Clay, 5.0 8.5 Limest 8.5 20.5 Shale, 20.5 21.0 Shale, 21.0 24.5 Shale, 24.5 34.0 Soft z 34.0 90.5 Limest	brown tan one weathered yellow/brown gray/brown dark gray ones one, gray frac	tured				HOLOGIC LOG
2.0 4.75 Clay, 4.75 5.00 Clay, 5.0 8.5 Limest 8.5 20.5 Shale, 20.5 21.0 Shale, 21.0 24.5 Shale, 24.5 34.0 Soft z 34.0 90.5 Limest 90.5 126.0 Chert	brown tan one weathered yellow/brown gray/brown dark gray ones one, gray frac	tured				HOLOGIC LOG
2.0 4.75 Clay, 4.75 5.00 Clay, 5.0 8.5 Limest 8.5 20.5 Shale, 20.5 21.0 Shale, 21.0 24.5 Shale, 24.5 34.0 Soft z 34.0 90.5 Limest 90.5 126.0 Chert	brown tan one weathered yellow/brown gray/brown dark gray ones one, gray frac	tured				HOLOGIC LOG
2.0 4.75 Clay, 4.75 5.00 Clay, 5.0 8.5 Limest 8.5 20.5 Shale, 20.5 21.0 Shale, 21.0 24.5 Shale, 24.5 34.0 Soft z 34.0 90.5 Limest 90.5 126.0 Chert	brown tan one weathered yellow/brown gray/brown dark gray ones one, gray frac	tured				HOLOGIC LOG
2.0 4.75 Clay, 4.75 5.00 Clay, 5.0 8.5 Limest 8.5 20.5 Shale, 20.5 21.0 Shale, 21.0 24.5 Shale, 24.5 34.0 Soft z 34.0 90.5 Limest 90.5 126.0 Chert 126.0 130.0 Shale	brown tan one weathered yellow/brown gray/brown dark gray ones one, gray frac	tured	(1) construc			
2.0 4.75 Clay, 4.75 5.00 Clay, 5.0 8.5 Limest 8.5 20.5 Shale, 20.5 21.0 Shale, 21.0 24.5 Shale, 24.5 34.0 Soft z 34.0 90.5 Limest 90.5 126.0 Chert 126.0 130.0 Shale	brown tan one weathered yellow/brown gray/brown dark gray ones one, gray frac VNER'S CERTIFICATIO 0-26-86	tured N: This water well was		ted, (2) recor	estructed, or (3) plug	ged under my jurisdiction and wa
2.0 4.75 Clay, 4.75 5.00 Clay, 5.0 8.5 Limest 8.5 20.5 Shale, 20.5 21.0 Shale, 21.0 24.5 Shale, 24.5 34.0 Soft z 34.0 90.5 Limest 90.5 126.0 Chert 126.0 130.0 Shale	brown tan one weathered yellow/brown gray/brown dark gray ones one, gray frac	tured N: This water well was		ted, (2) recor	estructed, or (3) plug	ged under my jurisdiction and wa
2.0 4.75 Clay, 4.75 5.00 Clay, 5.0 8.5 Limest 8.5 20.5 Shale, 20.5 21.0 Shale, 21.0 24.5 Shale, 24.5 34.0 Soft z 34.0 90.5 Limest 90.5 126.0 Chert 126.0 130.0 Shale	brown tan one weathered yellow/brown gray/brown dark gray ones one, gray frac vNER'S CERTIFICATIO 0-26-86	tured N: This water well was This Water Well ing Co.	Record was	ted, (2) recor and this record s completed of by (signati	istructed, or (3) plug d is true to the best n (mo/day/yr)	aged under my jurisdiction and was

records.