	WATER WELL R	ECORD F	orm WW		SA 82a-1212				
Dutler	FRACTION SW 1/4 NE	1/4 SW	ı	ION NUMBER			RANGE NU		
Distance and direction from nearest town or city			1/4	30	T 25	S	R 5E	E/W	
800 E. 10th El Dorado, Kansas									
2 WATER WELL OWNER: ERGON ASPHAULT & EMULSIONS, INC.									
RR#,ST. ADDRESS,BOX #: 800									
	orado, Kansas			CODE:		oplication Num	ber:		
WITH AN "X" IN SECTION BOX:	DEPTH OF POMPES				ELEVATION:				
N De	epth of groundwater Encount		ft.			ft.		ft.	
	'ELL'S STATIC WATER LEV			W LAND SU	RFACE MEASURE		, , ,		
O NE-	Pump test d Est. Yield: gpm				ft. after ft. after		of pumping @ of pumping @	gpm gpm	
W Wile	Bore Hole Diameter	in.	to	ft.		in.	to	ft.	
-   ×      w	ELL WATER 1085 USED				,	9. Dewaterir	44 1-1		
	1. Domestic 3. Feedlot				nd garden only		12. Other (Sp	ecify below	
	Irrigation 4. Industri  Was a chemical/bacteriological s			8. Air con YES	ditioning 19	D. <b>Monitorin</b> ; If yes, w	g well /hat_mo/day/yr_w:	as sample	
· · · · · · · · · · · · · · · · · · ·	ubmitted				Vater Well Disinfect		YES N		
5 TYPE OF CASING USED:	5. Wrought Iron	7. Fiberglass	9. Ot	her (Specify	below) CASING	JOINTS:	Glued	Threaded	
1. Steel 3. RPM (S	R) 6. Asbestos-Cement	t 8. Concrete til	e				Welded	Clamped	
2. PVC 4. ABS Blank casing diameter 8		t., Dia.	in.	to	ft., Dia		n. to	ft.	
Casing height by Casing	72 <sub>in</sub>	Weight:					-	It.	
Casing height helphaland surface: 12 in., Weight: lbs. / ft. Wall thickness or gauge No.  TYPE OF SCREEN OR PERFORATION MATERIAL:									
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify) N/A									
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)									
SCREEN OR PERFORATION OPENINGS ARE:									
1. Continuous slot 3. Mill slot 5. Gauzed wrapped			7. <b>To</b> r	ch cut	9. Drilled	holes	11. None ( o	en hole)	
2. Louvered shutter 4. Key p	ounched 6. Wire wra	pped	8. <b>Sa</b> v	w cut	10. Other (	specify) N/	A		
SCREEN - PERFORATION INTERVAL	From	ft. to		ft.,	From	ft.	to	ft.	
	From	ft. to		ft.,	From	ft.	to	ft.	
GRAVEL PACK INTERVALS:	From	ft. to		ft.,	From	ft.	to	ft.	
	From	ft. to		ft.,	From	ft.	to	ft.	
6 GROUT MATERIALS: 1. Neat	cement 2. Ce	ment Grout	3	. Bentonite	Otl	ner bente	onite hole plu	g	
Grout Intervals: From 6 ft. to 33 ft., From ft. to ft., From ft. to ft.								ft.	
What is the nearest source of possible of 1. <b>Septic tank</b> 4. <b>Laters</b>	7 Dit neiv	y 1	0. <b>Livestoc</b> l	k pens	13. Insecticid	e storage	15. Oil well/G	as well	
1. Septic tank 4. Lateral miles				uel storage 14. Abandon water well 16. Other (specify below)					
2. Sewer lines 5. Cess Pool N/A								<b>\</b>	
3. Watertight sewer line 6. Seepage pit 5. Feed yard 12. Fertilizer storage  Direction from well? How many feet?									
From To	LITHOLOGIC LOG		From	То			GIC LOG		
			6	33	bentonite hole	plug	·····		
			L	L					
Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and									
was completed on (mo/day/year) 6/25/2015 and this record is true to the best of my knowledge and belief.									
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 6/26/2015									
under the business name of Harp Well and Pump Service by (signature)  Todd S. Harp									