

WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL:		Fraction County: BUTLER	Section Number NE 1/4 SE 1/4 SE 1/4 34	Township Number T 25 S	Range Number R 6 E		
Distance and direction from nearest town or city street address of well if located within city? 4009 County Side							
2 WATER WELL OWNER:		CLARENCE MATTAL					
RR#, St. Address, Box #:		4009 COUNTRY SIDE					
City, State, ZIP Code:		WICHITA KS 67218					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 158 ft. ELEVATION NA Depth(s) Groundwater Encountered 1. 70 ft. 2. 125 ft. 3. 158 ft. WELL'S STATIC WATER LEVEL 20 ft. below land surface measured on mo/day/yr 81.10.94 Pump test data: Well water was NA ft. after 10 hours pumping gpm Est. Yield gpm : Well water was 10 ft. after 10 hours pumping gpm Bore Hole Diameter 10 in. to 158 ft., and 10 in. to 158 ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No					
5 TYPE OF BLANK CASING USED:		1 Steel PVC	3 RMP (SR)	5 Wrought iron	8 Concrete tile		
		4 ABS		6 Asbestos-Cement	9 Other (specify below)		
				7 Fiberglass	CASING JOINTS: Glued Clamped Welded Threaded		
Blank casing diameter		5 in. to 118 ft.	Dia	in. to	ft. Dia in. to ft.		
Casing height above land surface		12 in.	weight	lbs./ft. Wall thickness or gauge No. SDR 24			
TYPE OF SCREEN OR PERFORATION MATERIAL:							
1 Steel		3 Stainless steel	5 Fiberglass	8 RMP (SR)	10 Asbestos-cement		
2 Brass		4 Galvanized steel	6 Concrete tile	9 ABS	11 Other (specify)		
1 Continuous slot		Mill slot		5 Gauzed wrapped	12 None used (open hole)		
2 Louvered shutter		4 Key punched		6 Wire wrapped	8 Saw cut		
				7 Torch cut	9 Drilled holes		
					10 Other (specify)		
SCREEN-PERFORATED INTERVALS:		From 118 ft. to 158 ft.	From	From	ft. to		
		From	ft. to	From	ft. to		
GRAVEL PACK INTERVALS:		From 25 ft. to 158 ft.	From	ft. to	ft. to		
		From	ft. to	ft. to	ft. to		
6 GROUT MATERIAL:		Neat cement	2 Cement grout	3 Bentonite	4 Other		
Grout Intervals:		From 4 ft. to 25 ft.	From	ft. to	ft. to		
What is the nearest source of possible contamination:							
1 Septic tank		4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well		
2 Sewer lines		5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well		
3 Watertight sewer lines		6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)		
13 Insecticide storage							
Direction from well? NORTH WEST How many feet? 300							
FROM	TO	LITHOLOGIC LOG		FROM	TO	PLUGGING INTERVALS	
8	1	TOP SOIL					
1	2	YELLOW CLAY					
2	7	YELLOW SHALE					
7	10	SANDSTONE					
10	12	LIMESTONE					
12	13	YELLOW SHALE					
13	14	LIMESTONE					
14	15	GRAY SHALE					
15	28	LIMESTONE					
28	30	GRAY SHALE					
30	33	LIME SHALE					
33	75	SANDY LIME					
75	84	GRAY SHALE / LIME					
88	95	BROWN SHALE					
95		LIME / SHALE					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed , (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9/10/94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 464						This Water Well Record was completed on (mo/day/year) 9/10/94 by (signature) Robert L. Hay	