

1 LOCATION OF WATER WELL:

Fraction

NW 1/4 NW 1/4 SE 1/4

Section Number

17

Township Number

T 25 S

Range Number

R 8 E

County: BUTLER
Distance and direction from nearest town or city street address of well if located within city?

5N - 4E 1/4 ROSALIA AND HWY 54

2 WATER WELL OWNER:

BUCKLEY INDUSTRIES

RR#, St. Address, Box #


BOX 574 - WICHITA KS 67201

Board of Agriculture, Division of Water Resources

City, State, ZIP Code

Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:



4 DEPTH OF COMPLETED WELL: 50? ft. ELEVATION: -

Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft. ft.

WELL'S STATIC WATER LEVEL 3 ft. below land surface measured on mo/day/yr 08-23-90

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield 3.5 gpm: Well water was ft. after hours pumping gpm

Bore Hole Diameter 11.7 in. to ft. and in. to ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well

1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes No. X If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED: UNKNOWN

1 Steel 3 RMP (SR)
2 PVC 4 ABS

5 Wrought iron

6 Asbestos-Cement

7 Fiberglass

8 Concrete tile

9 Other (specify below)

CASING JOINTS: Glued ? Clamped ?

Welded

Threaded

Blank casing diameter 8 in. to 50? ft. Dia

Casing height above land surface in. weight

TYPE OF SCREEN OR PERFORATION MATERIAL: NA

1 Steel 3 Stainless steel
2 Brass 4 Galvanized steel

5 Fiberglass

6 Concrete tile

7 PVC

8 RMP (SR)

9 ABS

10 Asbestos-cement

11 Other (specify)

12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot 3 Mill slot
2 Louvered shutter 4 Key punched

5 Gauzed wrapped

6 Wire wrapped

7 Torch cut

8 Saw cut

9 Drilled holes

10 Other (specify)

11 None (open hole)

SCREEN-PERFORATED INTERVALS: From -2 ft. to 50? ft. From

From ft. to ft. From ft. to ft.

GRAVEL PACK INTERVALS: From GL ft. to 50? ft. From

From ft. to ft. From ft. to ft.

6 GROUT MATERIAL: NA 1 Neat cement

2 Cement grout

3 Bentonite 4 Other

5 Pit privy 6 Sewage lagoon 7 Feedyard 8 Livestock pens 10 Abandoned water well

11 Fuel storage 12 Fertilizer storage 13 Insecticide storage 14 Oil well/Gas well

15 Other (specify below)

What is the nearest source of possible contamination:

1 Septic tank 4 Lateral lines
2 Sewer lines 5 Cess pool
3 Watertight sewer lines 6 Seepage pit

7 Pit privy

8 Sewage lagoon

9 Feedyard

10 Livestock pens

11 Fuel storage

12 Fertilizer storage

13 Insecticide storage

Direction from well?

14 Abandoned water well

FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS

* WELL DRILLED IN 1975 - CANT FIND ANY RECORD

LITHOLOGIC INFORMATION - UNKNOWN

8" WHITE-GREY-PLASTIC TYPE OF CASING PROB. 50'

DUG OUT AROUND CASING FOUND DRILL HOLES AND

GRAVEL PACK AT APPROX -2' GL.

DISINFECTED - BACK FILLED AROUND CASING WITH

5 SACKS BENTONITE - RAISED AREA 2' ABOVE GL - SLOPED AWAY FROM CASING -
FREE D.P. - TELEPHONE ^{TOP} SUGGESTED PLUGGING -

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 08-24-90 and this record is true to the best of my knowledge and belief. Kansas

Water Well Contractor's License No. 479 This Water Well Record was completed on (mo/day/year) 09-04-90

Under the business name of EBBERTS DRILLING by (signature) George Ebbert