

1 LOCATION OF WATER WELL: County: <u>Sedgwick</u>		Fraction: <u>NW 1/4 NW 1/4 SW 1/4</u>	Section Number: <u>6</u>	Township Number: <u>24</u> S	Range Number: <u>10</u> EW
Distance and direction from nearest town or city street address of well if located within city? <u>See Below</u>					
2 WATER WELL OWNER: <u>Brian's Body Shop, Inc.</u> RR#, St. Address, Box #: <u>7400 N. meridian</u> City, State, ZIP Code: <u>valley center, KS 67147</u> <u>360</u> Board of Agriculture, Division of Water Resources Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: <u>360</u> ft. ELEVATION: <u>9/19/95</u> ft.			
		Depth(s) Groundwater Encountered <u>100</u> ft. 2. <u>360</u> ft. 3. <u>9/19/95</u> ft. WELL'S STATIC WATER LEVEL <u>100</u> ft. below land surface measured on mo/day/yr Pump test data: Well water was <u>30</u> gpm. Well water was <u>360</u> ft. after <u>360</u> hours pumping <u>360</u> gpm Est. Yield <u>30</u> gpm. Well water was <u>360</u> ft. after <u>360</u> hours pumping <u>360</u> gpm Bore Hole Diameter <u>11</u> in. to <u>360</u> ft., and <u>360</u> in. to <u>360</u> ft. WELL WATER TO BE USED AS: 1 Domestic <u>1</u> 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes <u>X</u> No <u>X</u> ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes <u>X</u> No <u>X</u>			
		5 TYPE OF BLANK CASING USED: 1 Steel <u>2 PVC</u> 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued <u>X</u> Clamped 2 PVC <u>5</u> 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded Blank casing diameter <u>5</u> in. to <u>28</u> ft. Dia. <u>2.60</u> in. to <u>160</u> ft. Dia. <u>160</u> in. to <u>160</u> ft. Dia. Casing height above land surface <u>12</u> in. weight <u>2.60</u> lbs./ft. Wall thickness or gauge No. <u>160</u> PSI TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass <u>7 PVC</u> 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot <u>3 Mill slot</u> 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From <u>28</u> ft. to <u>360</u> ft. From <u>28</u> ft. to <u>360</u> ft. From <u>28</u> ft. to <u>360</u> ft. From <u>28</u> ft. to <u>360</u> ft. GRAVEL PACK INTERVALS: From <u>20</u> ft. to <u>360</u> ft. From <u>20</u> ft. to <u>360</u> ft. From <u>20</u> ft. to <u>360</u> ft. From <u>20</u> ft. to <u>360</u> ft.			
		6 GROUT MATERIAL: 1 Neat cement 2 Cement grout <u>3</u> 3 Bentonite 4 Other Grout Intervals: From <u>3</u> ft. to <u>12</u> ft. From <u>3</u> ft. to <u>12</u> ft. From <u>3</u> ft. to <u>12</u> ft. From <u>3</u> ft. to <u>12</u> ft. What is the nearest source of possible contamination: <u>1 Septic tank</u> 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Direction from well? <u>East</u> How many feet? <u>180</u>			
		FROM TO LITHOLOGIC LOG		FROM TO PLUGGING INTERVALS	
0	2	Top Soil			
2	12	clay			
12	21	fine sand			
21	22	clay			
22	360	med gravel			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>9-19-95</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>318</u> This Water Well Record was completed on (mo/day/yr) <u>9-20-95</u> under the business name of <u>Weninger Drilling, Inc.</u> by (signature) <u>Karrina Morrissey</u>					