1 LOC	ATION OF WA	ATER WELL:	FRACTION	Water Well Reco	rd Form WWC-1	Section Number	Township Number	Range Number
Sedgwick			NW 1/4	SW 1/4	SW 1/4	19	т 26 s	R 1E EW
Distance and direction frem nearest town or city street address of well if located within city?								
3/4 mile S. of 53rd N. & Meridian Wichita, Kansas								
2 WATER WELL OWNER: CITY OF WICHITA								
RRW, ST. ADRESS, BOX #: P.O. Box 9163 Board of Agriculture, Divivision of Water Resource								
i	Y, STATE, ZII		ta, Kansa	s		67277	Application Numbe	r: 950298
3 LOCA	TE WELL'S			IPLETED WELL	40		VATION:	
AN "X" IN SECTION BOX: Depth(s) groundwater Encountered 1 ft. 2 ft. 3 ft.								
WELL'S STATIC WATER LEVEL 13 FT. BELOW LAND SURFACE MEASURED ON modday/yr 09/28/1995								
1			Pump test		water was		ifter hours pum	
Est. Yield gpm: Well water was							after hours pum	• • • •
N Mile			e Hole Diameter	12 in.	to 40	ft.	and in.	to ft.
E WELL WATER TO BE USED AS: 5 Public water sup								njection well
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering							•	Other (Specify below)
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well								
		Wa	-	riological sample s	ubmitted to D	enartment? Yes	No X ; If yes, π	no/day/yr sample was
S submitted Water Well Disinfected? Yes X No								
5 TYPE OF CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped								
1 Ste	el	3 RMP (SR)		6 Asbestos-Cem		Other (Specify be		Velded
2 PV	C	4 ABS		7 Fiberglass		DR-26	•	hreaded
Blank o	asing Dian	neter 8 in.	to 20	ft., Dia	in.		ft., Dia in.	to ft.
Į.	•	ve land surface 24	in.	welght			Wall thickness or gauge No.	.332
TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement								
1 Sta	eel	3 Stainless Steel		5 Flberglass	1	RMP (SR)	11 other (specify	<i>i</i>)
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)								
SCREEN OR PERFORATION OPENING ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)								
1 Continous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes								
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)								
SCREEN-PERFORATION INTERVALS: from 20 ft. to 40 ft., From ft. to ft.								
from				_	t. to	ft., From	ft. to	ft.
	GRAV	EL PACK INTERVAL	S: from 20		ft. to 40	ft., From		ft.
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other bentonite hole plus								ft
Count Internal Property Proper								
Grout Intervals: From 0 ft. to 20 ft. From ft. to ft. From ft. ft. to ft. What is the nearest source of possible contamination: 10 Livestock pens 14 Abandon water well								
1 Septic tank 4 Lateral lines				7 Pit privy		11 Fuel sto		
				8 Sewage lagoon		12 Fertiliz	13 (Oil well/Gas well Other (specify below)
12 Tunnettelde et puna								
3 Watertight sewer lines 6 Seepage pit 9 Feedyard None Apparent Direction from well?								
FROM			HOLOGIC LOG		FROM	то	PLUGGING INTE	RVALS
0	2	topsoil						
2	10	clay						
10	20	fine to me	dium san	d				
20	40	medium to						
		and gravel						
	ļ			77				
								
	 						Company of the control of the contro	
	ļ						18 - COMPANIE SANCE CONTRACTOR AND	
	1							
	-							
	 					 		
	1	i						
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and								
was completed on (mo/day/year)								
Well Contractor's License No								
Jane Frederick								
janie drederick								