1 LOCATION OF WATER WELL:	FRACTION	Water Well Record	Form WWC-5	KSA 82a-1212		Donas Namban	
Ľ				Section Number	Township Number	Range Number	
Sedgwick	SW 1/4		E 1/4	19	т 26 s	R 1E E/W	
Distance and direction frem nearest town or city street address of well if located within city?							
East of Harbor	Isle, East	of lake	Wi	chita, F	Kansas		
	Y OF WICHIT						
1I	N. Main				Board of Agriculture, D	vivsion of Water Resource	
	hita, Kansa	1S		67277	Application Number	960025	
3 LOCATE WELL'S LOCATION WITH	4 DEPTH OF	WELL	42		EVATION:		
AN "X" IN SECTION BOX:	Depth(s) groundwa	•	1	it. Et.	2 ft.	3 ft.	
	WELL'S STATIC W				URFACE MEASURED ON mo/day/yr	02/15/1996	
			•		_		
NWNE	Pump test		vater was	ft.	after hours pum		
ا     یو	Est. Yield	gpm: Well w	water was	ft.	after hours pum	- 0	
E W	Bore Hole Diameter	~	to	ft.	and in.	to ft.	
= "     ,	WELL WATER 12	BE USED AS: 5	5 Public water	·supply	8 Air conditioning 11 I	njection well	
	1 Domestic	3 Feedlot 6	6 Oil fieid wat	er supply	9 Dewatering 12 C	Other (Specify below)	
SWSE	2 Irrigation		7 Lawn and g	• • •	10 Monitoring well	` • -	
	_	·		•		o/day/yr sample was	
\$ S	Was a chemical/bacte	riologicai sampie sui	bmitted to be	•		-	
	submitted	<del></del>		· · · · · · · · · · · · · · · · · · ·	· · · · · · · · · · · · · · · · · · ·	X No	
5 TYPE OF CASING USED:		5 Wrought iron	_	Concrete tile	CASING JOINTS: G	lued Clamped	
1 Steel 3 RMP (SR)		6 Asbestos-Cemen	ıt 9	Other (Specify	below)	/elded	
2 PVC 4 ABS		7 Fiberglass			T	hreaded	
Blank casing Diameter 8	• 4.	J	in.	4	↑ Tu. in	<b>&amp;</b>	
Casing height to be land surface 3	in. to	ft., Dia	in.	to	ft., Dia in.	to ft.	
		weight	-	lbs. / ft.	Wall thickness or gauge No.	4	
TYPE OF SCREEN OR PERFORA	ΓΙΟΝ MATERIAL:			PVC	10 Asbestos-ceme		
1 Steel 3 Stainless Steel		5 Fiberglass		RMP (SR)	11 other (specify	) N/A	
2 Brass 4 Galvanized stee	el	6 Concrete tile	9	ABS	12 None used (op	•	
SCREEN OR PERFORATION OPI	ENING ARE:	5 Gauz	ed wrapped		8 Saw cut	11 None (open hole)	
1 Continous slot 3 Mill sl			eu wrappeu wrapped		9 Drilled holes		
3 .vam s			••				
2 Louvered shutter 4 Key p		7 Torch	cut		10 Other (specify)		
SCREEN-PERFORATION INTERV	VALS: from	ft.	to	ft., Fron	m ft. to	ft.	
	from	ft.	fn	ft., Fro		ft.	
GRAVEL PACK INTER			to	ft., Fro	····	ft.	
	from		to	ft., Fro		ft.	
6 GROUT MATERIAL: 1 Neat		Cement grout		tonite		hole plug	
		-		-			
Grout Intervals: From 10 What is the pearest source of possible	ft. to 20	ft. From	ft. 1		ft. From	ft. to ft.	
What is the nearest source of possible		5 Dis		10 Livest		bandon water well	
1 Septic tank 4 Later	al lines	7 Pit privy		11 Fuel s	130	Dil well/Gas well	
2 Sewer lines 5 Cess	pool	8 Sewage lagor	8 Sewage lagoon			Other (specify below)	
	age pit	9 Feedyard		13 Insect	ticide storage		
a	pparent	-			How many feet?		
FROM TO	LITHOLOGIC LOG		FROM	то	PLUGGING INTER	OVALS	
TAVIII - V	Dillion				surface clay an		
- •			יח	1 '7	THE CIAV ALL	f) ×=	
<del>                                     </del>			0	2		u BIIU	
			2	10	cement grout		
			2 10	10 20	cement grout bentonite hole	plug	
			2	10	cement grout	plug	
			2 10	10 20	cement grout bentonite hole	plug	
			2 10	10 20	cement grout bentonite hole	plug	
			2 10	10 20	cement grout bentonite hole	plug	
			2 10	10 20	cement grout bentonite hole	plug	
			2 10	10 20	cement grout bentonite hole	plug	
			2 10	10 20	cement grout bentonite hole	plug	
			2 10	10 20	cement grout bentonite hole	plug	
			2 10	10 20	cement grout bentonite hole	plug	
			2 10	10 20	cement grout bentonite hole	plug	
			2 10	10 20	cement grout bentonite hole	plug	
			2 10	10 20	cement grout bentonite hole	plug	
			2 10	10 20	cement grout bentonite hole	plug	
			2 10	10 20	cement grout bentonite hole	plug	
7 CONTRACTOR'S OR LANDOWNE	AND CERTIFICATION. This	a water well was (1	2 10 20	10 20 42	cement grout bentonite hole chlorinated san	plug d and gravel	
CONTRACTOR SURLANDOWNER	r's CERTIFICATION: Thi	s water well was (1	2 10 20 20 I) constructe	10 20 42	cement grout bentonite hole chlorinated san  ructed, or (3) plugged under m	plug d and gravel	
was completed on (mo/day/year)	02/15/	1996	10 20 20 1) constructe	10 20 42 42 ed, (2) reconstrord is true to t	cement grout bentonite hole chlorinated san  ructed, or (3) plugged under me	plug d and gravel  y jurisdiction and belief. Kansas Water	
was completed on (mo/day/year) Well Contractor's License No	02/15/ 236	1996 This Water Well Re	10 20 20 20 3) constructe and this rece	10 20 42 42 ed, (2) reconstructed is true to tompleted on (n	ructed, or (3) plugged under mithe best of my knowledge and mo/day/yr)	plug d and gravel  y jurisdiction and belief. Kansas Water	
was completed on (mo/day/year)	02/15/ 236	1996 This Water Well Re	10 20 20 20 3) constructe and this rece	10 20 42 42 ed, (2) reconstructed is true to tompleted on (n	ructed, or (3) plugged under mithe best of my knowledge and mo/day/yr)	plug d and gravel  by jurisdiction and belief. Kansas Water	