1 LOCATION OF WATER WELL:			FRACTION	1	W	HET WELL RECO	ora Form ww	VC-3	Section Number	Toy	vnship Number	Range	Number	
Sedgwick		- 1	SW	1/4	NW	1/4	SE 1/	4	19	,	26 s	. 1	E _{E/W}	
	direction frem nearest town or cit	y street :		ll if loca									<u> </u>	
East	t of Harbor	Tel	e. Ea	e+	of 1	ako	ı	Ti.	chita,	Kancac	•			
			WIC		_	unc	· · · · · ·	1	CHICA,	Nansas				
L			Main	** * *	-						Board of Agriculture, D	ivivsion of Water	Resource	
CITY, STA			, Ka	nga	c				67277		Application Numbe			
	VELL'S LOCATION WITH	4 D	EPTH OF	701	1665	AWELL	42			LEVATION		9000	<u> </u>	
DOCLETE !!	SECTION BOX:		pth(s) gro				1		it. Ei	LEVATION 2		3		
I + ┌	· · · · · · · · · · · · · · · · · · ·		, .					ет			ft.	-	ft.	
		WEL	L'S STAT								ASURED ON mo/day/yr	_	/1996	
	NWNE			n p te st			water was		ft.	after	hours pum		gpm	
ا ۽		Est. Y			gpm;	Well	water was	3	ft.	after	hours pum	ping	g p m	
l ag w ⊢	E	Bore l	Hole Diam	eter	ς .	in.	to		ft.	and	in.	to	ft.	
							5 Public w			8 Air con	-	njection well		
l ı	sw SE		Domestic		3 Feed				ter supply	9 Dewater	-	Other (Specify	y below)	
			Irrigation		4 Indu			•	arden only	10 Monito	_			
	S			/bacte	riologica	i sample s	submitted to) De	epartment? Yes		No 🗶 ; If yes, m	o/day/yr sam	ple was	
submitted Water Well Disinfected? Yes X No														
₩	OF CASING USED:					ought iron			Concrete tile				amped	
1 Steel 3 RMP (SR)						6 Asbestos-Cement 9 Other (Specif								
2 PVC	4 ABS				7 Fibe	rglass					Т	hreaded		
Blank casing	Diameter 8	in.	to		ft.,	Dia		in.	to	ft. ,	Dia in.	to	ft.	
		6		in.,		weight			lbs. / ft.	Wall thick	mess or gauge No.			
TYPE OF SCREEN OR PERFORATION MATERIAL:									PVC		10 Asbestos-ceme			
1 Steel 3 Stainless Steel									RMP (SR)		11 other (specify	11 other (specify) N/A		
2 Brass	4 Galvanized stee				6 Conci	rete tile		9	ABS		12 None used (or	en hole)		
SCREEN OR PERFORATION OPENING ARE:						5 Gauzed wrapped				8 Saw	cut	11 None (open hole)	
1 Continous slot 3 Mill slot						6 Wire wrapped				9 Dril	led holes			
2 Louvered shutter 4 Key punched						7 Torch cut				10 Otl	her (specify)	'A		
SCREEN-PERFORATION INTERVALS: from						ft. to			ft., Fro	m	ft. to		ft.	
from			ı.	ft. to				ft., From		ft. to		ft.		
GRAVEL PACK INTERVALS: from			1	ft. to			ft., From			ft. to		ft.		
from				ft. to				ft., Fro			ft. to			
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other bentonite hole plug											plug			
Grout Intervals: From 10 ft. to 20 ft. From ft. to ft. From ft. to										prug ft.				
What is the nearest source of possible co					16.	I TOZII		11.		tock pens		bandon wate		
1 Septic tank 4 Lateral				7 Pit privy			11 Fuel		-4					
2 Sewer lines 5 Cess po		nool	nool		8 Sewage lagoo		oon .					Oil well/Gas well Other (specify below)		
3 Watertigl	age pit		9 Feedyard					13 Insec	ticide stora		oner (speen)	Delow)		
Direction fro	- Stop.				-	ccuyana				Uow	many fact?			
	om well? None A	LITHO	LOGIC I	LOG			FRO	M	ТО	110W	many feet? PLUGGING INTE	RVALS		
							0		2	surfa	ce clay an			
							2		10		t grout			
	V						10		20		nite hole	plua		
							20		42		inated san		gravel	
										<u></u>		_ W.I.V.	3-4-61	
													-	
	7													
⁷ CONTR	ACTOR'S OR LANDOWNER	R'S CERT	IFICATION	:_This	water v	well was ((1) constru	ıcte	ed, (2) reconst	ructed, or ((3) <u>plugged</u> under m	y jurisdictio	n and	
was comp	leted on (mo/day/year)	**********	<u>02/1</u>	<u>,5/.1</u>	<u>996</u>		. and this i	reco	ord is true to t	the best of	my knowledge and	belief. Kans	sas Water	
Well Contr	ractor's License No	<u>236</u>	5	Т	his Wat	ter Well R	Record was	s co	empleted on (r	mo/day/yr).	02/20	<u>)/96</u>		
Under the	business name of H.	ırp	weTT"	kI	gmu.	Serv	ice,	Ι'n	l.C by (sig	nature)	0 0	, ,	,	
											Jane F	rederich	ર્ષ	
											U			