


1 LOCATION OF WATER WELL: Sedgwick	FRACTION SW NW SE NE SW 1/4 1/4	Section Number 7	Township Number T 26 S	Range Number R 1E E/W
Distance and direction from nearest town or city street address of well if located within city? 6502 6205 N. Bella Road Wichita, Kansas				
2 WATER WELL OWNER: WEDAKIND, Randy RR#, ST. ADDRESS, BOX #: 6205 N. Bella Road 6502 CITY, STATE, ZIP CODE: Wichita, Kansas		Board of Agriculture, Division of Water Resource Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF COMPLETED WELL 43 ft. ELEVATION:			
	Depth(s) groundwater Encountered 1 ft. 2 ft. 3 ft.			
	WELL'S STATIC WATER LEVEL 20 FT. BELOW LAND SURFACE MEASURED ON 03/05/1996			
	Pump test data: Well water was 1 ft. after 2 hours pumping 3 gpm			
Est. Yield 12 gpm		Well water was 43 ft. after 4 hours pumping 5 gpm		
Bore Hole Diameter 12 in.		to 43 ft. and 6 in. to 7 ft.		
WELL WATER TO BE USED AS:				
1 Domestic		5 Public water supply		
3 Feedlot		6 Oil field water supply		
2 Irrigation		7 Lawn and garden only		
4 Industrial		8 Air conditioning		
6 Concrete tile		9 Dewatering		
7 Fiberglass		10 Monitoring well		
8 RMP (SR)		11 Injection well		
9 ABS		12 Other (Specify below)		
Was a chemical/bacteriological sample submitted to Department? Yes <input type="checkbox"/> No <input checked="" type="checkbox"/> ; If yes, mo/day/yr sample was submitted				
Water Well Disinfected? Yes <input checked="" type="checkbox"/> No <input type="checkbox"/>				
5 TYPE OF CASING USED:				
1 Steel		3 RMP (SR)		5 Wrought iron
2 PVC		4 ABS		6 Asbestos-Cement
Blank casing Diameter 5 in. to 23 ft., Dia		Casing height above land surface 12 in., weight 2.35 lbs. / ft.		7 Fiberglass
TYPE OF SCREEN OR PERFORATION MATERIAL:		SCREEN OR PERFORATION OPENING ARE:		8 Concrete tile
1 Steel		3 Mill slot		9 Other (Specify below)
3 Stainless Steel		4 Key punched		CASING JOINTS:
2 Brass		5 Gauzed wrapped		Glued <input checked="" type="checkbox"/> Clamped
4 Galvanized steel		6 Wire wrapped		Welded
6 Concrete tile		7 Torch cut		Threaded
SCREEN-PERFORATION INTERVALS:		8 Saw cut		SDR-26
from 23 ft. to 43 ft., From		9 Drilled holes		Blank casing Diameter 5 in. to 23 ft., Dia
GRAVEL PACK INTERVALS:		10 Other (specify)		Casing height above land surface 12 in., weight 2.35 lbs. / ft.
from 23 ft. to 43 ft., From		11 None (open hole)		TYPE OF SCREEN OR PERFORATION MATERIAL:
from 23 ft. to 43 ft., From		12 None used (open hole)		1 Steel
from 23 ft. to 43 ft., From		13 Insecticide storage		3 Stainless Steel
from 23 ft. to 43 ft., From		14 Abandon water well		5 Fiberglass
from 23 ft. to 43 ft., From		15 Oil well/Gas well		6 Concrete tile
from 23 ft. to 43 ft., From		16 Other (specify below)		7 Fiberglass
from 23 ft. to 43 ft., From				8 RMP (SR)
from 23 ft. to 43 ft., From				9 ABS
from 23 ft. to 43 ft., From				CASING JOINTS:
from 23 ft. to 43 ft., From				Glued <input checked="" type="checkbox"/> Clamped
from 23 ft. to 43 ft., From				Welded
from 23 ft. to 43 ft., From				Threaded
from 23 ft. to 43 ft., From				SDR-26
from 23 ft. to 43 ft., From				Blank casing Diameter 5 in. to 23 ft., Dia
from 23 ft. to 43 ft., From				Casing height above land surface 12 in., weight 2.35 lbs. / ft.
from 23 ft. to 43 ft., From				TYPE OF SCREEN OR PERFORATION MATERIAL:
from 23 ft. to 43 ft., From				1 Steel
from 23 ft. to 43 ft., From				3 Stainless Steel
from 23 ft. to 43 ft., From				5 Fiberglass
from 23 ft. to 43 ft., From				6 Concrete tile
from 23 ft. to 43 ft., From				7 Fiberglass
from 23 ft. to 43 ft., From				8 RMP (SR)
from 23 ft. to 43 ft., From				9 ABS
from 23 ft. to 43 ft., From				CASING JOINTS:
from 23 ft. to 43 ft., From				Glued <input checked="" type="checkbox"/> Clamped
from 23 ft. to 43 ft., From				Welded
from 23 ft. to 43 ft., From				Threaded
from 23 ft. to 43 ft., From				SDR-26
from 23 ft. to 43 ft., From				Blank casing Diameter 5 in. to 23 ft., Dia
from 23 ft. to 43 ft., From				Casing height above land surface 12 in., weight 2.35 lbs. / ft.
from 23 ft. to 43 ft., From				TYPE OF SCREEN OR PERFORATION MATERIAL:
from 23 ft. to 43 ft., From				1 Steel
from 23 ft. to 43 ft., From				3 Stainless Steel
from 23 ft. to 43 ft., From				5 Fiberglass
from 23 ft. to 43 ft., From				6 Concrete tile
from 23 ft. to 43 ft., From				7 Fiberglass
from 23 ft. to 43 ft., From				8 RMP (SR)
from 23 ft. to 43 ft., From				9 ABS
from 23 ft. to 43 ft., From				CASING JOINTS:
from 23 ft. to 43 ft., From				Glued <input checked="" type="checkbox"/> Clamped
from 23 ft. to 43 ft., From				Welded
from 23 ft. to 43 ft., From				Threaded
from 23 ft. to 43 ft., From				SDR-26
from 23 ft. to 43 ft., From				Blank casing Diameter 5 in. to 23 ft., Dia
from 23 ft. to 43 ft., From				Casing height above land surface 12 in., weight 2.35 lbs. / ft.
from 23 ft. to 43 ft., From				TYPE OF SCREEN OR PERFORATION MATERIAL:
from 23 ft. to 43 ft., From				1 Steel
from 23 ft. to 43 ft., From				3 Stainless Steel
from 23 ft. to 43 ft., From				5 Fiberglass
from 23 ft. to 43 ft., From				6 Concrete tile
from 23 ft. to 43 ft., From				7 Fiberglass
from 23 ft. to 43 ft., From				8 RMP (SR)
from 23 ft. to 43 ft., From				9 ABS
from 23 ft. to 43 ft., From				CASING JOINTS:
from 23 ft. to 43 ft., From				Glued <input checked="" type="checkbox"/> Clamped
from 23 ft. to 43 ft., From				Welded
from 23 ft. to 43 ft., From				Threaded
from 23 ft. to 43 ft., From				SDR-26
from 23 ft. to 43 ft., From				Blank casing Diameter 5 in. to 23 ft., Dia
from 23 ft. to 43 ft., From				Casing height above land surface 12 in., weight 2.35 lbs. / ft.
from 23 ft. to 43 ft., From				TYPE OF SCREEN OR PERFORATION MATERIAL:
from 23 ft. to 43 ft., From				1 Steel
from 23 ft. to 43 ft., From				3 Stainless Steel
from 23 ft. to 43 ft., From				5 Fiberglass
from 23 ft. to 43 ft., From				6 Concrete tile
from 23 ft. to 43 ft., From				7 Fiberglass
from 23 ft. to 43 ft., From				8 RMP (SR)
from 23 ft. to 43 ft., From				9 ABS
from 23 ft. to 43 ft., From				CASING JOINTS:
from 23 ft. to 43 ft., From				Glued <input checked="" type="checkbox"/> Clamped
from 23 ft. to 43 ft., From				Welded
from 23 ft. to 43 ft., From				Threaded
from 23 ft. to 43 ft., From				SDR-26
from 23 ft. to 43 ft., From				Blank casing Diameter 5 in. to 23 ft., Dia
from 23 ft. to 43 ft., From				Casing height above land surface 12 in., weight 2.35 lbs. / ft.
from 23 ft. to 43 ft., From				TYPE OF SCREEN OR PERFORATION MATERIAL:
from 23 ft. to 43 ft., From				1 Steel
from 23 ft. to 43 ft., From				3 Stainless Steel
from 23 ft. to 43 ft., From				5 Fiberglass
from 23 ft. to 43 ft., From				6 Concrete tile
from 23 ft. to 43 ft., From				7 Fiberglass
from 23 ft. to 43 ft., From				8 RMP (SR)
from 23 ft. to 43 ft., From				9 ABS
from 23 ft. to 43 ft., From				CASING JOINTS:
from 23 ft. to 43 ft., From				Glued <input checked="" type="checkbox"/> Clamped
from 23 ft. to 43 ft., From				Welded
from 23 ft. to 43 ft., From				Threaded
from 23 ft. to 43 ft., From				SDR-26
from 23 ft. to 43 ft., From				Blank casing Diameter 5 in. to 23 ft., Dia
from 23 ft. to 43 ft., From				Casing height above land surface 12 in., weight 2.35 lbs. / ft.
from 23 ft. to 43 ft., From				TYPE OF SCREEN OR PERFORATION MATERIAL:
from 23 ft. to 43 ft., From				1 Steel
from 23 ft. to 43 ft., From				3 Stainless Steel
from 23 ft. to 43 ft., From				5 Fiberglass
from 23 ft. to 43 ft., From				6 Concrete tile
from 23 ft. to 43 ft., From				7 Fiberglass
from 23 ft. to 43 ft., From				8 RMP (SR)
from 23 ft. to 43 ft., From				9 ABS
from 23 ft. to 43 ft., From				CASING JOINTS:
from 23 ft. to 43 ft., From				Glued <input checked="" type="checkbox"/> Clamped
from 23 ft. to 43 ft., From				Welded
from 23 ft. to 43 ft., From				Threaded
from 23 ft. to 43 ft., From				SDR-26
from 23 ft. to 43 ft., From				Blank casing Diameter 5 in. to 23 ft., Dia
from 23 ft. to 43 ft., From				Casing height above land surface 12 in., weight 2.35 lbs. / ft.
from 23 ft. to 43 ft., From				TYPE OF SCREEN OR PERFORATION MATERIAL:
from 23 ft. to 43 ft., From				1 Steel
from 23 ft. to 43 ft., From				3 Stainless Steel
from 23 ft. to 43 ft., From				5 Fiberglass
from 23 ft. to 43 ft., From				6 Concrete tile
from 23 ft. to 43 ft., From				7 Fiberglass
from 23 ft. to 43 ft., From				8 RMP (SR)
from 23 ft. to 43 ft., From				9 ABS
from 23 ft. to 43 ft., From				CASING JOINTS:
from 23 ft. to 43 ft., From				Glued <input checked="" type="checkbox"/> Clamped
from 23 ft. to 43 ft., From				Welded
from 23 ft. to 43 ft., From				Threaded
from 23 ft. to 43 ft., From				SDR-26
from 23 ft. to 43 ft., From				Blank casing Diameter 5 in. to 23 ft., Dia
from 23 ft. to 43 ft., From				Casing height above land surface 12 in., weight 2.35 lbs. / ft.
from 23 ft. to 43 ft., From				TYPE OF SCREEN OR PERFORATION MATERIAL:
from 23 ft. to 43 ft., From				1 Steel
from 23 ft. to 43 ft., From				3 Stainless Steel
from 23 ft. to 43 ft., From				5 Fiberglass
from 23 ft. to 43 ft., From				6 Concrete tile
from 23 ft. to 43 ft., From				7 Fiberglass
from 23 ft. to 43 ft., From				8 RMP (SR)
from 23 ft. to 43 ft., From				9 ABS
from 23 ft. to 43 ft., From				CASING JOINTS:
from 23 ft. to 43 ft., From				Glued <input checked="" type="checkbox"/> Clamped
from 23 ft. to 43 ft., From				Welded
from 23 ft. to 43 ft., From				Threaded
from 23 ft. to 43 ft., From				SDR-26
from 23 ft. to 43 ft., From				Blank casing Diameter 5 in. to 23 ft., Dia
from 23 ft. to 43 ft., From				Casing height above land surface 12 in., weight 2.35 lbs. / ft.
from 23 ft. to 43 ft., From				TYPE OF SCREEN OR PERFORATION MATERIAL:
from 23 ft. to 43 ft., From				1 Steel
from 23 ft. to 43 ft., From				3 Stainless Steel
from 23 ft. to 43 ft., From				5 Fiberglass
from 23 ft. to 43 ft., From				6 Concrete tile
from 23 ft. to 43 ft., From				7 Fiberglass
from 23 ft. to 43 ft., From				8 RMP (SR)
from 23 ft. to 43 ft., From				9 ABS
from 23 ft. to 43 ft., From				CASING JOINTS:
from 23 ft. to 43 ft., From				Glued <input checked="" type="checkbox"/> Clamped
from 23 ft. to 43 ft., From				Welded
from 23 ft. to 43 ft., From				Threaded
from 23 ft. to 43 ft., From				SDR-26
from 23 ft. to 43 ft., From				Blank casing Diameter 5 in. to 23 ft., Dia
from 23 ft. to 43 ft., From				Casing height above land surface 12 in., weight 2.35 lbs. / ft.
from 23 ft. to 43 ft., From				TYPE OF SCREEN OR PERFORATION MATERIAL:
from 23 ft. to 43 ft., From				1 Steel
from 23 ft. to 43 ft., From				3 Stainless Steel
from 23 ft. to 43 ft., From				5 Fiberglass
from 23 ft. to 43 ft., From				6 Concrete tile
from 23 ft. to 43 ft., From				7 Fiberglass
from 23 ft. to 43 ft., From				8 RMP (SR)
from 23 ft. to 43 ft., From				9 ABS
from 23 ft. to 43 ft., From				CASING JOINTS:
from 23 ft. to 43 ft., From				Glued <input checked="" type="checkbox"/> Clamped
from 23 ft. to 43 ft., From				Welded
from 23 ft. to 43 ft., From				Threaded
from 23 ft. to 43 ft., From				SDR-26
from 23 ft. to 43 ft., From				Blank casing Diameter 5 in. to 23 ft., Dia
from 23 ft. to 43 ft., From				Casing height above land surface 12 in., weight 2.35 lbs. / ft.
from 23 ft. to 43 ft., From				TYPE OF SCREEN OR PERFORATION MATERIAL:
from 23 ft. to 43 ft., From				1 Steel
from 23 ft. to 43 ft., From				3 Stainless Steel
from 23 ft. to 43 ft., From				5 Fiberglass
from 23 ft. to 43 ft., From				6 Concrete tile
from 23 ft. to 43 ft., From				7 Fiberglass
from 23 ft. to 43 ft., From				8 RMP (SR)
from 23 ft. to 43 ft., From				9 ABS
from 23 ft. to 43 ft., From				CASING JOINTS:
from 23 ft. to 43 ft., From				