1 LOC	TION OF W	ATER WELL:	FRACTION	W	Mer Well Record	. Form WWC-	Section Number	Township Number	Range Number	
H	Sedgy	ai ck	SE 1/4	SW	1/4 N	IE 1/4	34		10	
Distance		frem nearest town or city str				15 1/4	34	T 26 s	R IE E/W	
$\overline{}$					<u>Kansas</u>					
	TER WELL	IAC CL	ISH, Ken							
RR#, ST. ADRESS, BOX#: 2730 E. 33rd N. Board of Agriculture, Divivsion of Water Resource										
	, STATE, ZII		ta, Kans					Application Numbe	r:	
	TE WELL'S I	LOCATION WITH	DEPTH OF CO			126		EVATION:		
	11020110	N	Depth(s) ground			1	ft.	2 ft.	3 ft.	
			ELL'S STATIC		EVEL 15	FT FT	. BELOW LAND SI	URFACE MEASURED ON mo/day/yr	04/10/1996	
	NW	NE	Pump to	est data:	Well w	vater was	ft.	after hours pum	ping gpm	
Est. Yield					gpm: Well water was ft.			after hours pum	ping gpm	
1 Mile	/	E Bor	e Hole Diameter	12	in.	to 126	ft.	and in.	to ft.	
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well								njection well		
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify belo							Other (Specify below)			
	1 7		2 Irrigation	4 Indu	strial	7 Lawn and g	garden only	10 Monitoring well		
	Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was									
S submitted Water Well Disinfected? Yes X No										
5 TYPE OF CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped										
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (Specify below) Welded										
	 asing Diam		40.25		-		DR-26			
			to 26	ft.,	Dia	in.	to	ft., Dia in.	to ft.	
Casing height above land surface 12 in., weight 2.35 lbs./ft. Wall thickness or gauge No214 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement										
1 Ste		3 Stainless Steel	N WATERIAL.	5 Fiber	plass		RMP (SR)			
2 Bra		4 Galvanized steel		6 Conc			ABS	11 other (specify	•	
				o Conc			ADS	12 None used (op	•	
		RFORATION OPENIN	NG ARE:			ed wrapped		8 Saw cut	11 None (open hole)	
	nous slot	3 Mill slot			6 Wire	wrapped		9 Drilled holes		
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)										
SCREEN-PERFORATION INTERVALS: from 26 ft. to 126 ft., From ft. to ft.										
			from		ft.	to	ft., Froi	m ft. to	ft.	
GRAVEL PACK INTERVALS: from 24					ft. to 126		ft., Fro		ft.	
from ft. to ft., From							m ft. to	ſt.		
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other bentonite hole plug										
Grout Intervals: From 4 ft. to 24 ft. From ft. to ft. From ft. to										
What is the nearest source of possible contamination:						10 Livest		bandon water well		
1 Septic tank 4 Lateral lines			ies	7 Pit privy			11 Fuel s	torage 15 C	oil well/Gas well	
2 Sewer lines 5 Cess pool			ı	8 Sewage lagoon			12 Fertil		16 Other (specify below)	
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage None Apparent										
Direction from well? How many feet?										
FROM	ТО		HOLOGIC LOC	}		FROM	то	PLUGGING INTER	RVALS	
0	4	topsoil				T				
4	15	clay								
15	18	fine sand				1				
18	110	shale				1	1 +			
	126	limestone					1	***************************************		
		TTWCSCOUG				-				
						+				
						 				
						<u> </u>	+ +			
							+ +			
						1	1			
						ļ				
						_	1			
<u> </u>										
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and										
was completed on (mo/day/year)										
Well Contractor's License No23.6										
Under the business name of Harp Well & Pump Service, Inc by (signature)										
Jane Frederick										