

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Sedgwick		1/4 SE 1/4 NW 1/4	35	T 26 S	R 1 EW
Distance and direction from nearest town or city street address of well if located within city? 4111 East 37th Street North, Wichita, Kansas					
2 WATER WELL OWNER:		Koch Industries, Inc.		01968501	MW-28
RR#, St. Address, Box # :		4111 East 37th Street North		Board of Agriculture, Division of Water Resources	
City, State, ZIP Code :		Wichita, Kansas 67208		Application Number:	
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 29.0 ft. ELEVATION: Approx. Surface 1350			
		Depth(s) Groundwater Encountered 1. 6.4 ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL: 6.4 ft. below land surface measured on mo/day/yr 04/26/96			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield N/A gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter: 8.25 in. to 29 ft. and in. to ft.			
		WELL WATER TO BE USED AS:			
		5 Public water supply 8 Air conditioning 11 Injection well			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes No X			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued Clamped			
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile		Welded			
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below)		Threaded X			
Blank casing diameter 2 in. to 4 ft. Dia. in. to ft. Dia. in. to ft.					
Casing height above land surface 36 in. weight lbs./ft. Wall thickness or gauge No. Schedule 40					
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)					
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)			
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes					
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From 4 ft. to 29 ft. From ft. to ft.					
GRAVEL PACK INTERVALS: From 3 ft. to 29 ft. From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 0 ft. to 1.5 ft. From 1.5 ft. to 3.0 ft. From ft. to ft.					
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well			
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage					
Direction from well?		How many feet?			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	0.3	Silt, Dark Brown			
0.3	5.5	Clay, Dark Brown			
5.5	8.0	Clayey Sand, Brown			
8.0	9.5	Fine to Medium Sand, Brown			
9.5	15.8	Clay, Brown			
15.8	16.0	Fine to Medium Sand, Brown			
16.0	18.0	Clay, Olive-Gray			
18.0	19.0	Fine to Coarse Sand, Brown			
19.0	20.5	Clay, Brown			
20.5	21.5	Clay, Olive-Gray			
21.5	23.0	Clay, Brown			
23.0	24.0	Weathered Shale, Medium Gray			
24.0	29.0	Weathered Shale, Dark Gray			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 1 constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 04/23/96 and this record is true to the best of my knowledge and belief. Kansas					
Water Well Contractor's License No. 416		This Water Well Record was completed on (mo/day/yr) 15-22-96			
under the business name of Terracon Consultants, Inc.		by (signature) <i>Steve Fischer</i>			