LICCA	TION OF W	TER WELL:	FRACTION			ord Form WW	C-5 KSA 82a-1212 Section Number	T		Range Number
٣				NW SE		IE Meno				1 179
Distance	Sedgy and direction			1/4 SAN		<b>神名</b> 1/4		T 26 s		R 1E E/W
Distance and direction from nearest town or city street address of well if located within city?  414 W. 41st N. Wichita, Kansas										
	TERWELL		W10	Cnita,	Kans	as				
WATER WELL OWNER: CARSON, Edwin CARSTENS  RRM, ST. ADRESS, BOX#: 414 W. 41st N.  Board of Agriculture, Divivsion of Water Resource										
CITY, STATE, ZIP CODE: Wichita, Kansas Application Number:										
$\overline{}$		OCATION WITH		COMPLETE	DWELL	30	ft. E	LEVATION:	OLI I GLIZZOCE :	
	" IN SECTIO			undwater Enc		1	it. E	2 ft.	. 3	ft.
l t			WELL'S STAT			_		SURFACE MEASURED ON mo	_	/25/1996
				p test data:		water was	ft.		ırs pumping	, 23, 1330 gpm
l '	NW	NE	Est. Yield	gpm:		l water was	ft.		rs pumping	gpm
M M		X   J.	Bore Hole Diame		in.	to 30	ft.	and	in. to	ft.
ĭ ¼		E	WELL WATER			5 Public wa		8 Air conditioning	11 Injection	
1.			1 Domestic	3 Feed			water supply	9 Dewatering	-	Specify below)
	SW		2 Irrigation	4 Indu	strial	7 Lawn and	l garden only	10 Monitoring well		
	₩as a chemical/bacteriological sample submitted to Department? Yes No 🗶 ; If yes, mo/day/yr samp								yr sample was	
S submitted Water Well Disinfected? Yes X								No		
5 TY	PE OF CA	SING USED:		5 Wro	ught iron	1	8 Concrete tile	CASING JOINTS	S: Glued	X Clamped
1 Steel 3 RMP (SR)					stos-Cem	ent	9 Other (Specify	y below)	Welded	
2 PVC		4 ABS		7 Fibe	rglass		SDR-26		Threade	ed
	asing Diam	_	in. to 25	ft.,	Dia		in. to	ft., Dia	in. to	ft.
				in.,	weight	2.35	lbs. / ft.	Wall thickness or gauge		.214
1 Ste		N OR PERFORA	TION MATERIA	AL: 5 Fiber	oloss		7 <u>PVC</u> 8 RMP (SR)		tos-cement	
2 Bra		3 Stainless Steel 4 Galvanized stee		6 Conci	_		9 ABS	11 other	•	->
				o conci				8 Saw cut	used (open hole	e) None (open hole)
1	n OK PEI	RFORATION OPI 3 Mill sl				uzed wrappe re wrapped	1	9 Drilled hoies	11 /	tone (open note)
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)  SCREEN-PERFORATION INTERVALS: from 2.5 ft to 3.0 ft From ft to 3.0 ft.										
SCREE	N-PERFO	RATION INTERV		25		ft. to 30	ft., Fr		ft. to	ft.
GRAVEL PACK INTERVALS: from 24				24	ft. to ft. to 30		ft., Fr		ft. to	ft.
from					n. to 30		ft., Fr		ft. to ft. to	ft.
from ft. to ft., From ft. to ft.  6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other										
Crout Intervals: France A									to ft.	
		source of possible		144	r I Olli	•		stock pens		n water well
1 Septic tank 4 Lateral lines			7	Pit privy		11 Fuel	storage	15 Oil well/Gas well		
2 Sewer lines 5 Cess pool			8 8	8 Sewage lagoon		12 Fert	ilizer storage	16 Other (specify below)		
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage										
	n from we			·				How many feet?	100	
FROM			LITHOLOGIC L	OG		FROM	1 TO		INTERVALS	
0 2	2	topsoil								
	10	clay								
10	30	mealum t	o coarse	sand						
						+		47.04 47.77		
						<u> </u>			A 1.4. P	
						<u> </u>		LATE VI		
								1.1.1.1		
										1
7 CO	NTRACTO	R'S OR LANDOWNE	R'S CERTIFICATION	: This water	well was	(1) constru	cted, (2) recons	structed, or (3) plugged (	under mv iuri	sdiction and
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year)										
Well Contractor's License No236 This Water Well Record was completed on (mo/day/yr)										
Under the business name of Harp Well Rump Service Inc by (signature)										
								Toda	d S. F	tarp