I la oca	TION ON W		FRACTI	OD!	Wa	ter Well Reco	rd Form WW	/C-5	KSA 82a-1212	1			
1 LOCATION OF WATER WELL:									Section Number	Township Number	Range Number		
Sedgwick NE 1/4 Distance and direction from nearest town or city street address of well if it				NE		SE 1/	4	19	т 26 s	R 1E EW			
l		•	-			-							
		Seneca				nsas							
ш	TER WELL (mant.	DY, Jam										
RR#, ST. ADRESS, BOX#: 4921 N. Seneca Board of Agriculture, Divivsion of Water Res											Divivsion of Water Resource		
CITY, STATE, ZIP CODE: Wichita, Kansas										Application Number:			
	TE WELL'S I ' IN SECTIO	OCATION WITH	4 DEPTH (35			EVATION:			
A	IN SECTIO	N N	Depth(s) g	roundw	ater Enc	ountered	1		ft.	2 ft.	3 ft.		
H			WELL'S STA	ATIC W	ATER L	EVEL 1	.5	FT. B	BELOW LAND SUI	RFACE MEASURED ON mo/day/yr	06/19/1990	6	
	NW	NE	P	ump test	data:	Well	water was		ft.	after hours pu	mping gp	pm	
	1		Est. Yleld		gpm:	Well	water was		ft.	after hours pu	mping gj	pm	
13 w	-	E	Bore Hole Dia	umeter	12	in.	to 35		ft.	and in.	to fi	Ł.	
= "			WELL WAT	ER TO E	BE USED	AS:	5 Public w	ater s	supply	8 Air conditioning 11	Injection well		
١,	- sw	s	1 Domest	tic	3 Feed	lot	6 Oil field	wate	r supply	9 Dewatering 12	Other (Specify below)		
2 Irrigation					4 Industrial 7 Lawn and garden only				rden only 1	10 Monitoring well			
Was a chemical/bacteriological sample submitted to Department? Yes No ✗; If yes, mo/day/yr sample										mo/day/yr sample was			
S submitted Water Well Disinfected? Yes X No											X No		
5 TYPE OF CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped													
1 Steel 3 RMP (SR)					ooughto moss				Other (Specify b		Welded		
2 PVC	•	4 ABS			7 Fibe	rglass			R-26	•	Threaded		
	_ sing Diam		in. to 2	E		•			to	ft. Dia in.	4. 4		
l .	-	_		_	ft.,	Dia		in.		,	to ft.		
		N OR PERFORA		in., RIAL:		weight	2.35		eus. / II. PVC	Wall thickness or gauge No. 10 Asbestos-cen	.214		
1 Stee		3 Stainless Steel		5 Fiber	glass			RMP (SR)	11 other (speci				
2 Bras		4 Galvanized stee	el		6 Conci	rete tile			ABS	12 None used (e	•		
	_				_	£ C				8 Saw cut	11 None (open hole	4)	
SCREEN OR PERFORATION OPENING ARE: 1 Continous slot 3 Mill slot						5 Gauzed wrapped 6 Wire wrapped				9 Drilled holes			
1	red shutte									10 Other (specify)			
ŀ						7 Tor				10 Ouler (specify)		_	
SCREE	N-PERFO	RATION INTERV	ALS: fire	om 25		f	t. to 35		ft., From	ft. to	, 1	ft.	
from				ft. to				ft., From		1	ft.		
				om 24	-				ft., Fron		•	ft.	
Jone		DD 4 N 4	fire				ft. to		ft., Fron			<u>t. </u>	
GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 4 ft. to 2.4 ft. From ft. to 6 From ft. to													
			ft. to 24		ft.	From		ft. to		ft. From		ft.	
What is the nearest source of possible contamination:			77 DM I				10 Livesto		14 Abandon water well				
1 Septic tank 4 Lateral lines				7 Pit privy				11 Fuel st	13	15 Oil well/Gas well			
2 Sewer lines 5 Cess pool					8 Sewage lagoon					zer storage 16 cide storage	16 Other (specify below)		
3 Wate	rtight sew	er lines 6 Seepa	age pit		91	Feedyard			13 Hisecu	ciue storage			
	n from we									How many feet? 100			
FROM	TO		LITHOLOGI	CLOG			FRO	M	TO	PLUGGING INTI	ERVALS		
0	2	topsoil									·		
2	15	clay											
15	35	medium t	o coars	se s	<u>and</u>					*************************************			
										.,			
				_									
									:				
											·		
						· · · · · ·							
7 (0)					-								
100										ucted, or (3) plugged under			
Was c	ompleted	on (mo/day/year)		42.2.Q.	-4 204-11	and this	reco	ord is true to th	he best of my knowledge an	d belief. Kansas Wate On 196	er	
Under	ontracto	r's License No		a r	Pump	iter Well Se ru	Record wa	s co Tn	mpleted on (m	no/day/yr)	(M./		
Olidei	trie Dusii	iess hallie olaan	uw 5 yıyı	·····	A.MMY.			A1A67	m by (sign	To dd	l Harr		
Under the business name of Harp Well & Pump Service. Inc by (signature) Todd &. Harp													