		T	Water Well Record	Form WWC-5	KSA 82a-1212		,
ப்	WATER WELL:	FRACTION		_	Section Number		Range Number
	gwick	NE 1/4	NE 1/4 N	E 1/4	21	T 26 s	R 1E E/W
		ity street address of well if lo	•				
	N. Hydraul		<u>chita, Kan</u> s	sas		· · · · · · · · · · · · · · · · · · ·	
WATER WELL OWNER: WOOLSEY, Wayne RR#, ST. ADRESS, BOX #: 5301 N. Hydraulic -Board of Agriculture, Divivsion of Water Resource							
CITY, STATE,		l N. Hydrai hita, Kans				Application Numbe	
	'S LOCATION WITH		AND SECONDARY ELL	29	ft. E	LEVATION: ground le	
AN "X" IN SEC			vater Encountered	1	ft.	2 ft.	3 ft.
l † [) X	WELL'S STATIC V		FT.	BELOW LAND	SURFACE MEASURED ON mo/day/yr	08/07/1996
		Pump tes	t data: Well w	ater was	ft.	after hours pum	
		Est. Yield	91	ater was	ft.	after hours pum	ping gpm
§ w	E	Bore Hole Diameter		to	ft.	and in.	to ft.
		WELL WATER		Public water		•	njection well
s	vsie	1 Domestic		Oil field was Lawn and g		· ·	Other (Specify below)
		2 Irrigation	·	Ū	•	10 Monitoring well s No ; If yes, m	o/dov/www.comple.wee
	S	submitted	eriological sample sub	mutted to De	•	Vater Well Disinfected? Yes	no/day/yr sample was X No
5 TYPE OF	CASING USED:	,	5 Wrought iron	8	Concrete tile		lued Clamped
1 Steel	3 RMP (SR)		6 Asbestos-Cemen		Other (Specif	• • • • •	Velded
2 PVC	4 ABS		7 Fiberglass			T	`hreaded
Blank casing Di	ameter 12	in. to	ft., Dia	in.	to	ft., Dia in.	to ft.
	ove land surface		weight		lbs. / ft.	Wall thickness or gauge No.	
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 11 other (specify) 27 / 78							
1 Steel	3 Stainless Steel		6 Concrete tile			11 other (specify	· N/A
2 Committee of the state of the							•
SCREEN OR PERFORATION OPENING ARE: 5 Gauze 1 Continuus slot 3 Mill slot 6 Wire v					rapped 11 vone (open new)		
2 Louvered shu	5 WILLS						1-
SCHEEN BEDEON ATION INTERVAL							
SCREEN-I ERI	CRATION INTER		ft. 1		ft., Fr		ft.
from GRAVEL PACK INTERVALS: from				ft. to ft., Fi			ft.
from				ft. to ft., From ft. to ft., From			ft. ft.
6 GROUT MA	TERIAL: 1 Neat	cement 2 (Cement grout	3 Ben	tonite	4 Other	
Grout Intervals: From 0 ft. to 5 ft. From ft. to ft. From ft. to ft.							
What is the nearest source of possible contamination:						bandon water well	
1 Septic tank 4 Lateral lines							Dil well/Gas well
2 Sewer lines 5 Cess pool 3 Watertight sewer lines 6 Seepage pit			8 Sewage lagoon 12 Fertilizer 13 Insecticid		uuzer storage 16 (ecticide storage	Other (specify below)	
Direction from	-	age pit	9 Feedyard			•	
FROM TO	LITHOLOGIC LOG		FROM	то	How many feet? 400 PLUGGING INTE	RVALS	
				0	5	cement	
				5	15	bentonite hole	plug
				15	29	chlorinated san	d and gravel
					_		
					+		,
					<u> </u>		
							- 7-70
				1			
7 CONTRAC	TOR'S OR LANDOWNE	er's certification: Th	is water well was (1) construct	ed, (2) recons	structed, or (3) plugged under n	ny jurisdiction and
was complete	ed on (mo/day/year	_{r)} Q8/Q7/	1996	and this rec	ord is true to	the best of my knowledge and	belief. Kansas Water
Well Contrac	tor's License No	<u> </u>	This Water Well Re	cord was c	ompleted on	(mo/day/yr)	2./.Y.D
under th e bu	Siless name of Mi	arp Well &	·*·**********	.₩.₩.,∦	Dy (Si	gnature) Todd S	Harr