1 LOCATION OF WATER WELL:	FRACTION	Water Well Record	Form WWC-5	KSA 82a-1212 Section Number	Township Number	Range Number	
Sedgwick	NW 1/4	NE 1/4 N	TW 1/4	22	26	1 179	
Distance and direction frem nearest town or city at			W 2/1		T 20 s	R IE E/W	
2121 E. 53rd St. N. Wichita, Kansas							
WATER WELL OWNER: MILLER, Larry							
RRW, ST. ADRESS, BOX#: 2121 E. 53rd St. N. Board of Agriculture, Divivsion of Water Resource							
	ta, Kansa				Application Number		
LOCATE WELL'S LOCATION WITH  AN "X" IN SECTION BOX:	DEPTH OF COM Depth(s) groundwa		80	ft. ELEV	VATION:	3 ft.	
	Depun(s) groundwa VELL'S STATIC W		1 1 FT.		2 ft. FACE MEASURED ON mo/day/yr	3 ft. 08/22/1996	
	Pump test	_	vater was		fter hours pum	-	
NWNE	st. Yield		vater was		fter hours pum		
E Bo	ore Hole Diameter	12 in.	to 80	ft.	and in.	to ft.	
= "	ELL WATER TO B	E USED AS:	5 Public water	supply 8	Air conditioning 11 Is	njection well	
swse	1 Domestic		6 Oil fieid wat		•	other (Specify below)	
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well						(1)	
Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No							
5 TYPE OF CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped							
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other					<u> </u>	elded & Champeu	
2 PVC 4 ABS		7 Fiberglass	SI	DR-26	T	hreaded	
Blank casing Diameter 5 in	L to 30	ft., Dia	in.	to	ft., Dia in.	to ft.	
Casing height above land surface 12 TYPE OF SCREEN OR PERFORATION	in.,	weight 2			Vall thickness or gauge No. 10 Asbestos-ceme	.214	
TYPE OF SCREEN OR PERFORATION MATERIAL:  1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 11 other (specify)							
2 Brass 4 Galvanized steel		6 Concrete tile		ABS	12 None used (op		
SCREEN OR PERFORATION OPENING ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)							
1 Continous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes							
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)							
SCREEN-PERFORATION INTERVALS: from 30 ft. to 80 ft., From ft. to ft.							
from			to	ft., From	ft. to	ft.	
GRAVEL PACK INTERVALS: from 24			to 80	ft., From	ft. to	ft.	
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other bentonite hole pl					<u> </u>		
	ft. to 24	ft. From					
What is the nearest source of possible contamination:		R. From	ft. t	o 10 Livestoci	ft. From k pens 14 A	ft. to ft. bandon water well	
1 Septic tank 4 Lateral lines		7 Pit privy		11 Fuel stor	rage 15 C	15 Oil well/Gas well	
2 Sewer lines 5 Cess pool		8 Sewage lagoon		12 Fertilize	100	ther (specify below)	
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage							
Direction from well? Northwes		FROM TO How n		How many feet? 150	nany feet? 150 PLUGGING INTERVALS		
0 4 topsoil	THOLOGIC LOG		FRON	10	FLUGGING INTER	, valo	
4 20 clay							
20 25 fine sand							
25 40 medium sa	nd		<b>_</b>				
40 80 shale							
					AMAY S. A. San		
				-			
				<del> </del>			
7 CONTRACTOR'S OF LANDOWNERS CERTIFICATION. This water well was (4) constructed (2) reconstructed or (2) plugged under my jurisdiction and							
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year)							
Well Contractor's License No?	236·	This Water Well Re	scord was co	empleted on (mo	/day/yr)	/96	
Under the business name of.从品工					ture)		
Todd S. Harp							