Loca	TION OF WA	TER WELL:	FRACTION	Water W	eli Record Form V		on Number	Township Number	Range Number	
Sedgwick			NE 1/4	NE 1	4 SW	1/4	21	т 26 s	1	
		and I-135			City, Ka	nsas				
⊔	ATER WELL C		CITY, CI					Decard of A subscibe	re, Divivalon of Water Resource	
	ST. ADRESS,		N. Hydra					-		
CIT	Y, STATE, ZIP	code: Park	<u>City, Ka</u>				219	Application N	umber: 960236	
		OCATION WITH	DEPTH OF CO		•	D ft		VATION:	_	
AN "X" IN SECTION BOX: Depth(s) groundwater Encountered 1 ft. 2 ft. 3 ft.										
lî		Wi	ELL'S STATIC V	WATER LEV	EL 15	FT. BELO	W LAND SUR	FACE MEASURED ON mo/day/	m 08/26/1996	
	NW	NE	Pump te	st data:	Well water w	18	ft. s	ifter hours	p umping g pm	
			. Yield	gpm:	Well water w	AS	ft.	after hours	pumping gpm	
MIN A	,	E Bor	re Hole Diameter	12	in. to 5	0	ft.	and	in. to ft.	
= '	'l ! .	λ	ELL WATER TO	BE USED AS	s: 5 Public	water supp	dy t	8 Air conditioning	11 Injection well	
١.			1 Domestic	3 Feedlot	6 Oil fie	ld water su	pply !	Dewatering	12 Other (Specify below)	
11	SW		2 Irrigation	4 Industri	al 7 Lawn	and garden	only 1	0 Monitoring well		
		l w	as a chemical/bac	teriological sa	mple submitted	to Departn	nent? Yes	No X ; If yo	es, mo/day/yr sample was	
S submitted Water Well Disinfected? Yes X No										
CACANA ANNO AND										
	TYPE OF CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (Specify below) Welded									
2 PV		4 ABS		7 Flbergk		SDR-		/	Threaded	
	_		4. 30					• N-		
ł .	asing Diam	•		ft. ,	Dia	in. to		,	n. to ft.	
Casing height above land surface 12 in., weight 2.35 lbs./ft. Wall thickness or gauge No214 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement										
1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 11 other (specify)										
2 Br		4 Galvanized steel		6 Concrete	tile	9 ABS	` ,	· -	d (open hole)	
		•	NG ADE					8 Saw cut	11 None (open hole)	
		RFORATION OPENI	NG ARE:		5 Gauzed wrap	•		9 Drilled holes	11 None (open note)	
1	inous slot	3 Mill slot			6 Wire wrappe	ų				
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)										
SCREEN-PERFORATION INTERVALS: from 20 ft. to 50 ft., From ft. to ft.										
1			from		ft. to		ft., From		to ft.	
	GRAV!	EL PACK INTERVAL	LS: from 2	0	ft. to 5()	ft., From		to ft.	
			from		ft. to		ft., From		to ft.	
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other bentonite hole plug										
l .	ntervals:		t. to 20	ft. Fro	m	ft. to	40.7.1	ft. From	ft. to ft.	
						10 Livesto		14 Abandon water well		
1 -		4 Lateral li	nes				11 Fuel storage		15 Oil well/Gas well	
	er lines	5 Cess poo	ol	8 Sewage lagoon			12 Fertiliz	_	16 Other (specify below)	
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage None Apparent										
Direction from well? How many feet?										
FROM			HOLOGIC LOC	}	FR	ОМ	TO	PLUGGING IN	ITERVALS	
0	2	topsoil								
2	10	silty sand						WAR STATE OF THE S		
10	22	medium to	coarse	sand						
22	24	clay								
24	39	medium to	coarse	sand				***************************************		
39	50	shale								
								White of all		
7 ~	NTDACTO	Dicontant	CENTIES CATALON T	hie water wa	ll was (4)	tructod ") record	icted or /2\ pluseed	for my juriodistics and	
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) <u>constructed</u> , (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year)										
Well Contractor's License No23.5										
Unde	Under the business name of Harp Well & Pump Service									
Todd S. Harp										
	r the busi	ness name of.XAXI	p Well &	RumpS	ervice,	Inc	by (sign	ature)	& Harr	