1.00.	ION OF WA		FRACTION	Water Well Re	cord Form WWC-	Section Number		Range Number	
ĽJ							Township Number	1	
	Sedgw		NE 1/4	NE 1/4	SW 1/4	21	т 26 в	R 1W E/W	
Distance and direction frem nearest town or city street address of well if located within city?									
49th N. and I-135 Park City, Kansas									
_	ER WELL O		ITY, CI						
LJ	ST. ADRESS,		•				Board of Agriculture, D	Divivsion of Water Resource	
_					4.0		Application Number	#: 90UZ30	
				MPLETED WEL			VATION:		
AN "X" IN SECTION BOX: Depth(s) groundwater Encountered 1 ft. 2 ft. 3 ft.									
		WE	LL'S STATIC V	VATER LEVEL	12 F	T. BELOW LAND SUR	FACE MEASURED ON mo/day/yr	08/30/1996	
	NW	NE .	Pump te	st data: We	ll water was	ft. s	ifter hours pun	ıping gpm	
l			Yield	gpm: We	ell water was	ft.	after hours pun	ıp ing gpm	
M M		Bore	Hole Diameter	12 in.	to 40	ft.	and in.	to ft.	
Į≅w		//IE			5 Public wat	_		Injection well	
1 1 1 1 1 1								Other (Specify below)	
1 1 - sw								Suiter (Speedy Below)	
			2 Irrigation			•	•		
Was a chemical/bacteriological sample submitted to Department? Yes No ✗; If yes, mo/day/yr sample was									
S submitted Water Well Disinfected? Yes X No									
5 TYPE OF CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped									
1 Stee	l	3 RMP (SR)		6 Asbestos-Ce	ment	9 Other (Specify be	elow)	Welded	
2 PVC	:	4 ABS		7 Fiberglass	5	SDR-26	1	Threaded	
	_ sing Diam		to 20	ft. Dia	in		ft. Dia in.	to ft.	
	•	-		,		- **	,		
		e land surface 12 N OR PERFORATION	in. • Matediai	, weight	2.35	7 PVC	Wall thickness or gauge No. 10 Asbestos-cem	.214	
1			MAI EKIAL:	5 Fiberglass		8 RMP (SR)			
1 Stee	el	3 Stainless Steel		_			11 other (specif	· ·	
2 Bras	is	4 Galvanized steel		6 Concrete tile		9 ABS	12 None used (o	pen hole)	
SCREE	N OR PER	REFORATION OPENIN	G ARE:	5 G	auzed wrapped		8 Saw cut	11 None (open hole)	
1 Conti	nous slot	3 Mill slot		6 W	ire wrapped		9 Drilled holes		
2 Lauve	red shutter		od				10 Other (specify)		
1		• •			orch cut		10 Calci (speelly)	_	
SCREEN-PERFORATION INTERVALS: from 20 ft. to 40 ft., From ft. to ft.									
1			from		ft. to	ft., From	ft. to	ft.	
GRAVEL PACK INTERVALS: from 20 ft. to 40						ft., From	ft. to	ft.	
			from		ft. to	ft., From	ft. to	ft.	
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other bentonite hole plug									
Grout Intervals: From 0 ft. to 20 ft. From ft. to ft. From ft. to ft.									
What is the nearest source of possible contamination: 10 Livestock pens 14 Abandon water well									
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage									
1 -				8 Sewage lagoon			- 13	15 Oil well/Gas well 16 Other (specify below)	
12 Transfeld at annual									
3 wateright sewer fines 6 Seepage pit 9 receivant None Apparent									
Direction from well? How many feet?									
FROM	то		HOLOGIC LOG	`	FROM	ТО	PLUGGING INTE	RVALS	
0	2	topsoil							
2	10	silty sand							
10	40	medium to	coarse :	sand					
40	50	shale							
							The second secon		
 					 				
									
					1				
l							THE PARTY OF THE P		
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and									
was completed on (mo/day/year)									
Well Contractor's License No23.6									
Under	the busir	ness name of HAKE	Well &	Pump Ser	vice. I	אב by (sian	ature)		
				_		, , , ,	Todd I	8. Harp	
							00000		