Linca	TION OF W	ATER WELL:	FRACTION	Water Well Recor	d Form WWC-5	KSA 82a-1212 Section Number	T	DN	
سرا			NA SE 145W				Township Number	Range Number	
- Dist	Sedgr				SW 1/4	19	_ <sub>T</sub> 26 <sub>s</sub>	R 1E EW	
Distance and direction frem nearest town or city street address of well if located within city?									
		r Isle Add			<u>Kansas</u>				
	TER WELL		MAN CONSTR					ATT . The	
RR#, ST. ADRESS, BOX#: 2338 Timbercreek Ct.  Board of Agriculture, Divivsion of Water Resource									
CITY, STATE, ZIP CODE: Wichita, Kansas Application Number:									
	TE WELL'S I		DEPTH OF COM		40		VATION:		
^``^	INSECTIO	N N	Depth(s) groundwa	iter Encountered	1	ft.	2 ft.	3 ft.	
lĪ			WELL'S STATIC WA	ATER LEVEL 1	8 гт.	BELOW LAND SUR	FACE MEASURED ON mo/day/yr	03/13/1997	
Pump test data: Well water was ft. after hours pumpin							nping gpm		
ا ا			Est. Yield	gpm: Well				nping gpm	
i i w	/ <b>k</b> /-		Bore Hole Diameter	12 in.	to 40	ft.	and in.	to ft.	
= "	X		WELL WATER TO E	E USED AS:	5 Public water	r supply 8	Air conditioning 11	Injection well	
Ι.			1 Domestic	3 Feedlot	6 Oil field wa	ter supply 9	Dewatering 12	Other (Specify below)	
	SW		2 Irrigation	4 Industrial	7 Lawn and g	arden only 1(	) Monitoring well		
	Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was								
L	S submitted Water Well Disinfected? Yes X No								
TYPE OF CASING HOPP.									
TYPE OF CASING USED:  5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (Specify below) Welded									
2 PV		4 ABS		7 Fiberglass	•		•	rveided Threaded	
1	-		<u></u>	_		DR-26			
	asing Diam	_	in. to 20	ft., Dia	in. Var	to No. 10	ft., Dia in.	to ft.	
				weight 2			Vall thickness or gauge No. 10 Asbestos-cem	.214	
FEVE									
(Person									
2 Comment of the Comm									
	n OK PE nous slot				zed wrapped		9 Drilled holes	11 None (open hole)	
1		3 Mill slo		6 WIF	e wrapped				
	red shutte	3 #		7 Torc	h cut		10 Other (specify)		
SCREEN-PERFORATION INTERVALS: from 20 ft. to 40 ft., From ft. to ft.									
from				ft. to		ft., From	ft. to	ft.	
	GRAV	EL PACK INTERV	ALS: from 20	ft. to 40		ft., From	ft. to	ft.	
from ft. to ft., From ft. to									
GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other bentonite hole plug									
								ft. to ft.	
What is the nearest source of possible contamination:					10 Livestoc	k pens 14 A	Abandon water well		
1 Septic tank 4 Lateral lines			l lines	7 Pit privy		11 Fuel sto	13	15 Oil well/Gas well	
2 Sewer lines 5 Cess pool			8 Sewage lagoon		12 Fertilize		16 Other (specify below)		
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage									
Direction from well? East How many feet? 12									
FROM		I	LITHOLOGIC LOG		FROM	ТО	PLUGGING INTE	RVALS	
0 2 15	2	sand							
2	15	clay							
15	20	medium s	and						
20	40	coarse s							
L									
					Ĭ				
					1	1		_ anamr-	
				-					
7 CONTRACTOR'S ON LANDOWNERS (SETURGATION). This water well was (4) constructed (2) reconstructed or (3) plugged under my jurisdiction and									
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year)									
was completed on (mo/day/year)									
Under the business name of Harp Well & Pump Service. Inc by (signature)									
- Time	and busin	TOTA HAILIE VI.ARM	mgAI.m.mm		mm.m.f#1#	vy (sigila	Jall S	Harr	
Todd S. Harp									