

AGES-GARY

5B-3

1 LOCATION OF WATER WELL: County: <u>SEDGEWICK</u>	Fraction <u>NW 1/4 NW 1/4 NE 1/4</u>	Section Number <u>34</u>	Township Number <u>T 26 S</u>	Range Number <u>R 1 E E/W</u>
---	---	-----------------------------	----------------------------------	----------------------------------

Distance and direction from nearest town or city street address of well if located within city?

2 WATER WELL OWNER: <u>WICHITA DISTRIBUTORS</u> RR#, St. Address, Box #: <u>3619 N. POPLAR</u> City, State, ZIP Code: <u>WICHITA, KS 67219</u>	Board of Agriculture, Division of Water Resources Application Number:
--	--

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: <u>20</u> ft. ELEVATION:
--	---

Depth(s) Groundwater Encountered 1. 11 ft. 2. 11 ft. 3. 11 ft.

WELL'S STATIC WATER LEVEL 11 ft. below land surface measured on mo/day/yr

Pump test data: Well water was 11 ft. after 11 hours pumping 11 gpm

Est. Yield 11 gpm: Well water was 11 ft. after 11 hours pumping 11 gpm

Bore Hole Diameter 8 1/4 in. to 11 in. and 11 in. to 11 in.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well

1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well SOIL BORING

Was a chemical/bacteriological sample submitted to Department? Yes 11 No 11; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes 11 No 11

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued <u>11</u> Clamped <u>11</u>
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below) <u>11</u>
2 PVC	4 ABS	7 Fiberglass	10 Asbestos-cement
Blank casing diameter <u>11</u> in. to <u>11</u> ft., Dia <u>11</u> in. to <u>11</u> ft., Dia <u>11</u> in. to <u>11</u> ft.			11 Other (specify) <u>11</u>
Casing height above land surface <u>11</u> in., weight <u>11</u> lbs./ft. Wall thickness or gauge No. <u>11</u>			12 None used (open hole)
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC	10 Asbestos-cement	
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify) <u>11</u>
SCREEN-PERFORATED INTERVALS: From <u>11</u> ft. to <u>11</u> ft., From <u>11</u> ft. to <u>11</u> ft., From <u>11</u> ft. to <u>11</u> ft.			
GRAVEL PACK INTERVALS: From <u>11</u> ft. to <u>11</u> ft., From <u>11</u> ft. to <u>11</u> ft., From <u>11</u> ft. to <u>11</u> ft.			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other <u>11</u>
Grout Intervals: From <u>11</u> ft. to <u>11</u> ft., From <u>11</u> ft. to <u>11</u> ft., From <u>11</u> ft. to <u>11</u> ft.				
What is the nearest source of possible contamination:	10 Livestock pens	14 Abandoned water well		
1 Septic tank	4 Lateral lines	7 Pit privy	11 Fuel storage	15 Oil well/Gas well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	12 Fertilizer storage	16 Other (specify below)
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	13 Insecticide storage	
Direction from well?	How many feet? <u>11</u>			

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
<u>0</u>	<u>10</u>	<u>DARK BROWN CLAY</u>	<u>0</u>	<u>1</u>	<u>CONCRETE</u>
<u>10</u>	<u>11</u>	<u>RED BROWN SAND</u>	<u>1</u>	<u>4</u>	<u>DIRT</u>
<u>11</u>	<u>20</u>	<u>RED BROWN CLAY</u>	<u>4</u>	<u>14</u>	<u>CONCRETE</u>
			<u>14</u>	<u>20</u>	<u>HOLE PLUG</u>

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>7-23-97</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>607</u> This Water Well Record was completed on (mo/day/yr) <u>8/5/97</u> under the business name of <u>DAVIS ENVIRONMENTAL DRILLING LLC</u> by (signature) <u>[Signature]</u>
--