LOCATION	OF WATER WELL:	FRACTION	Water Well Reco	rd Form WWC-5	KSA 82a-1212 Section Number	I	T	
Ľ	dgwick	NE 1/4	NE 1/4	NE 1/4	18	Township Number	Range Number	
	rection frem nearest town or city			NE 1/4	18	т 26 s	R 1E EW	
6101 N. Seneca Wichita, Kansas								
		ACK, Dave	III Ca, Ka.	HDAD				
RR#, ST. AD		N. Seneca				Board of Agriculture, D	Divivsion of Water Resource	
CITY, STAT	E, ZIP CODE: Wich:	nita, Kansas				Application Number:		
	LL'S LOCATION WITH 6 ECTION BOX:	DEPTH OF COM	PLETED WELL	40	ft. ELE	EVATION:		
AN "X" IN SI	N	Depth(s) groundwa		1	ft.	2 ft.	3 ft.	
		WELL'S STATIC WA			BELOW LAND SUI	RFACE MEASURED ON mo/day/yr	10/21/1998	
'	NWNE	Pump test of Est. Yield	****	water was		after hours pum		
₩ W		Sore Hole Diameter	gpm: Well 12 in.	water was	ft. ft.	after hours pum	. 0	
\(\frac{1}{2}\) w	! ; 12-1	VELL WATER TO B		to 40 5 Public water	_	and in. 8 Air conditioning 11 I	to ft. Injection well	
		1 Domestic	3 Feedlot	6 Oil field wa			Other (Specify below)	
	SW SE	2 Irrigation	4 Industrial	7 Lawn and g	arden only 1	0 Monitoring well		
Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sa							10/day/yr sample was	
		submitted			Wat	er Well Disinfected? Yes	X No	
5 TYPE O	F CASING USED:		5 Wrought iron		Concrete tile		dued X Clamped	
2 PVC	3 RMP (SR) 4 ABS		6 Asbestos-Ceme 7 Fiberglass	-	Other (Specify be	•	Velded	
Blank casing		n. to 25	•		DR-26		Threaded	
1 "	above land surface 12	_ _	ft., Dia	in. O 2 E	to lbs. / ft.	ft., Dia in. Wall thickness or gauge No.	to ft.	
Casing height above land surface 12 in., weight 2.35 lbs./ft. Wall thickness or gauge No214 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement								
1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 11 other (specify)								
2 Brass	4 Galvanized steel	6 Concrete tile	9	ABS	12 None used (or	pen hole)		
1	R PERFORATION OPEN	5 Gauzed wrapped			8 Saw cut 11 None (open hole)			
1 Continous slot 3 Mill slot 6 Wire wrs								
2 Louvered sl	, , , , , , , , , , , , , , , , , , ,		7 Toro	h cut		10 Other (specify)		
SCREEN-PERFORATION INTERVALS: from 25 ft. to 40 ft., From ft. to							ft.	
	DANEL DACE INTERNAL	from		to 4.0	ft., From		ft.	
G	RAVEL PACK INTERVA	ALS: from 24		t. to 40 t. to	ft., From ft., From		ft.	
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other bentonite hole plug							hole plug	
Grout Interva		ft. to 24	ft. From	ft. From ft. to		ft. From ft. to ft.		
What is the nearest source of possible contaminati		ontamination:			10 Livesto	ck pens 14 A	bandon water well	
1 Septic tank 4 Lateral lines			7 Pit privy		11 Fuel sto	15 (Dil well/Gas well	
2 Sewer lines	5 Cess po		8 Sewage lag	oon	12 Fertilizer storage 13 Insecticide storage		Other (specify below)	
o seepage pit								
Direction from well? Northwest FROM TO LITHOLOGIC LOG					How many feet? 80 TO PLUGGING INTERVALS			
0 4	sand			FROM	 	T DUGGING INTE	CVALS	
4 12	clay							
12 40	medium co	arse sand						
					ļ			
					 			
					+ +			
					 			
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year)								
Todd S. Harp								