

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Sedgewick		NE 1/4 NE 1/4 NW 1/4	34	T 26 S	R 1 E
Distance and direction from nearest town or city street address of well if located within city?					
2 WATER WELL OWNER: Unocal Corporation			Local ID No: TW-3		
RR#, St. Address, Box #: 1535 W. 13th Ave			Board of Agriculture, Division of Water Resources		
City, State, ZIP Code: Denver, CO 80204			Application Number: NA		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 20.0 ft. ELEVATION: 1327.35			
		Depth(s) Groundwater Encountered 1. Not Detected ft. 2. NA ft. 3. NA ft.			
		WELL'S STATIC WATER LEVEL 12.9 ft. below land surface measured on mo/day/yr 9/23/98			
		Pump test data: Well water was NA ft. after NA hours pumping NA gpm			
		Est. Yield NA gpm: Well water was NA ft. after NA hours pumping NA gpm			
		Bore Hole Diameter 6.25 in. to NA ft., and NA in. to NA ft.			
		WELL WATER TO BE USED AS:			
		5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes ☐ No ☒ If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes ☐ No ☒			
5 TYPE OF BLANK CASING USED:					
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued ☐ Clamped ☐ 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded ☐ 7 Fiberglass 7 PVC 10 Asbestos-cement 10 Asbestos-cement Flush Blank casing diameter 2.0 in. to 15.2 ft. Dia NA in. to NA ft. Dia NA in. to NA ft.					
Casing height above land surface -0.4 ft. weight NA lbs./ft. Wall thickness or gauge No. Schedule 40					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS:					
From 15.2 ft. to 19.5 ft. From NA ft. to NA ft. From NA ft. to NA ft. From NA ft. to NA ft.					
GRAVEL PACK INTERVALS:					
From 13.0 ft. to 21.0 ft. From NA ft. to NA ft. From NA ft. to NA ft. From NA ft. to NA ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other NA					
Grout Intervals: From 0.0 ft. to 3.0 ft. From 3.0 ft. to 13.0 ft. From NA ft. to NA ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) Industrial Activity					
Direction from well? Surrounded How many feet?					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0.0	1.0	Gravel Fill			
1.0	3.5	Sandy silt (ML)			
3.5	5.5	Cherty Sand (SC)			
5.5	37.0	Silty Clay (CH)			
37.0	40.0	SHALE			
Dan Smith of HLA completed form.					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8/1/91 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 102/581 This Water Well Record was completed on (mo/day/yr) 1/29/99 under the business name of Layne-Western by (signature) Steve Mitchell					