CO

				WELL RECORD	Form WWC-				1
	ON OF WAT		Fraction 1/4	SE ¼ SV		ction Number 33	Township		Range Number
County: SI	EDGWIC	from pagrant tour		SE 1/4 SV Idress of well if locate			<u> </u>	<u>s</u>	R 1-E E/W
		TH ST.FRAN			7219				
									
		NER: COLEMAN					Doord o	f Amulauda	Divinian of Mater Description
		(#:2111 E,						•	Division of Water Resources
City, State,	ZIP Code	WICHITA	A,KS	67219				ion Number:	
LOCATE	: WELL'S LO IN SECTION	I BOV.							
	N SECTION	1 De							3
ī	!	! w							
L	- NW	NE	Pump	test data: Well wat	er was	ft. a	ifter	hours pu	ımping gpm
1 1	1	Es	st. Yield	gpm: Well wat	er was	ft. a	ifter	hours pu	ımping gpm
* w -	1	l Bo	ore Hole Diame	ter. 7. ⊈ in. to	. 4 4 .	- 5 ft., .	and	in	i. to
₹ "	!		ELL WATER TO	O BE USED AS:	5 Public wat	er supply	8 Air condition	ing 11	Injection well
īL	- sw	SE	1 Domestic	3 Feedlot	6 Oil field w	ater supply	9 Dewatering	12	Other (Specify below)
	Ιx	%	2 Irrigation	4 Industrial					
1 1	i fi	ıjw	as a chemical/b	acteriological sample	submitted to [Department? Y	esNo	; If yes	, mo/day/yr sample was sub
			itted				ter Well Disinfe		No
5 TYPE O	F BLANK C	CASING USED:		5 Wrought iron	8 Conc	rete tile	CASING .	JOINTS: Glue	d Clamped
_ 1 Ste	el	3 RMP (SR)		6 Asbestos-Cement	9 Other	(specify below	v)	Weld	led
☆ PV0	С	4 ABS	24 5	7 Fiberglass			· · · · · · · · · · · · ·	x Thre	aded
Blank casin	ng diameter	4 ABS	to 34,5	ft., Dia	in. to	.	ft., Dia		in. to ft.
									lo
		R PERFORATION N		_	x ⁷ P'			Asbestos-ceme	
1 Stee	el	3 Stainless st	teel	5 Fiberglass		MP (SR)			
2 Bra	ISS	4 Galvanized	steel	6 Concrete tile	9 AI	· ·		None used (or	
SCREEN C	R PERFOR	RATION OPENINGS	ARE:	5 Gau	zed wrapped		8 Saw cut		11 None (open hole)
1 Cor	ntinuous slo	t X3 Mill s	slot 0 . 1 0	6 Wire	wrapped		9 Drilled hole	es	(open nois)
2 Lou	vered shutt	er 4 Key	punched		h cut				
		ED INTERVALS:	From 44			ft Fro	m	ft f	toft.
									toft.
G	RAVEL PA	CK INTERVALS:	From 44	• 5 ft. to .	27	ft. Fro	m	ft 1	toft.
_			From	ft. to					to ft.
6 GROUT	MATERIAL	: 1 Neat cerr				onite 4	Other		
Grout Interv	vals: From	n 20 ft.	to 0	Cement grout	7ft.	to. 20	ft. From		ft. toft.
What is the		urce of possible cor		r			tock pens	14 A	bandoned water well
1 Sep	otic tank	4 Lateral I	ines	7 Pit privy		11 Fuel	storage		il well/Gas well
₹ Sewer lines 5 Cess poo			• •		oon	12 Fertilizer storage 16 Other (specify below)			
3 Watertight sewer lines 6 Seepage			• •			13 Insecticide storage			
Direction fro	-	east				How ma		30	
FROM	TO		LITHOLOGIC L	.OG	FROM	TO		PLUGGING I	NTERVALS
0	6"	ASPHALT							
6"	2	CLAY FILI	 [₄						
2	2.5	CONCRETE		CLAY					
2.5	6	BRN SILTY		J					
6	10	BRN SILTY							——————————————————————————————————————
10	13	CLAYEY SA				1			
	• •			AND SATURA	יייע כואין	17			
13	20	FINE TO P			140 41	1			
20	30		•		ADCE	†	· · · · · · · · · · · · · · · · · · ·		
30	43.5			FINE TO CO	JAKOL	†			
- 43 ∤	5 44.	-		VE GREEN		 			
	44.5	WEATHER	ED SHALE			1			
						+			
						++			
						+ +			
	i					1			
									der my jurisdiction and was
		year) 22 4 9							owledge and belief. Kansas
Water Well	Contractor'	s License No	575	This Water V	Vell Record w			アーシェン	9
	usiness na			MENTAL SER		by (signa	12 11 12 12	Mel-	
				244 V and DOME clearly D	ages fill in blanks	undarlina ar airala	the correct answer	South ton three	copies to Kansas Department
INICTOLIC	TIONS: I Iss to	newriter or hall point pan	PLEASE PRESS EIL						