

Plugging Report


1 LOCATION OF WATER WELL: County: Saline Fraction: NE 1/4 NW 1/4 NE 1/4 Section Number: 20 Township Number: T 26 S Range Number: R 1 E

Distance and direction from nearest town or city street address of well if located within city?

301 W 53rd N

2 WATER WELL OWNER: Allie M. Mitchell
RR#, St. Address, Box #: 301 W 53rd N
City, State, ZIP Code: Wichita KS 67204 Board of Agriculture, Division of Water Resources
Application Number: none

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:



4 DEPTH OF COMPLETED WELL: 32 ft. ELEVATION: 1300

Depth(s) Groundwater Encountered 1. 16 ft. 2. 16 ft. 3. 16 ft.

WELL'S STATIC WATER LEVEL 16 ft. below land surface measured on mo/day/yr 1-12-99

Pump test data: Well water was 16 ft. after 16 hours pumping 16 gpm

Est. Yield 16 gpm: Well water was 16 ft. after 16 hours pumping 16 gpm

Bore Hole Diameter 16 in. to 16 ft., and 16 in. to 16 ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well

1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes X No X; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes X No X

5 TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped X

1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded X

2 PVC 4 ABS 7 Fiberglass Threaded X

Blank casing diameter 5 in. to 5 ft., Dia 5 in. to 5 ft., Dia 5 in. to 5 ft.

Casing height above land surface 0 in., weight 0 lbs./ft. Wall thickness or gauge No. 4/16

TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement

1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)

2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)

1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes

2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 999 ft. to 999 ft. From 999 ft. to 999 ft.

From 999 ft. to 999 ft. From 999 ft. to 999 ft.

GRAVEL PACK INTERVALS: From 999 ft. to 999 ft. From 999 ft. to 999 ft.

From 999 ft. to 999 ft. From 999 ft. to 999 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 16 ft. to 0 ft. From 0 ft. to 0 ft. From 0 ft. to 0 ft.

What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well

1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well

2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)

3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage

Direction from well? East How many feet? 25

FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS

32 16 Don't know 32 16

16 0 Cement Grout 16 0

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 1-12-99 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 477 This Water Well Record was completed on (mo/day/yr) 1-12-99 under the business name of Beard Pump & Well by (signature) Davis Beck