- Iraa			T the case	•	Water Well Rec	ord Form WWC-5					
1 LOCA		ATER WELL:	FRACTIO	E CE	_		Section Number	100000000000000000000000000000000000000	F	lange Number	
Dist	Sedg		1 -464			NW 1/4	32	т 26 s	R	1E <sub>E/W</sub>	
1		frem nearest town or cit			•						
		33rd N.			a, Kan	sas					
$\Box$	TER WELL ST. ADRESS	1101	VEDT, Li					Daniel of Ameloub	tura Dhahustan afi	W-A Passana	
1	Y, STATE, ZI	200	W. 33rd N. nita, Kansas					Board of Agriculture, Divivision of Water Resource			
T		LOCATION WITH			TED WELL	35	. FI	Application N	Number:		
	" IN SECTIO			r COMPLE oundwater E		1	ft. EI	LEVATION: 2 ft.	3	ft.	
l t			WELL'S STA			_		SURFACE MEASURED ON mo/day	_	15/1998	
11			1	mp test data:		water was	ft.	_	pumping	gpm	
	NW	NE	Est. Yield	gpr		l water was	ft.		pumping	gpm	
1 Mile	, X	E	Bore Hole Diar		.2 in.	to 35	ft.	and	in. to	ft.	
] = "			WELL WATE	R TO BE US	SED AS:	5 Public water	r supply	8 Air conditioning	11 Injection	well	
1 ,	sw	sac	1 Domesti	c 3 F	eedlot	6 Oil field wa	ter supply	9 Dewatering	12 Other (Sp	ecify below)	
			2 Irrigatio	n 4 In	ıdustrial	7 Lawn and g	arden only	10 Monitoring well			
1 +		S		l/bacteriolog	gical sample :	submitted to De	partment? Yes	No X; If y	es, mo/day/yr	sample was	
- 73	THE OF C		submitted				w		Yes X	No	
5 TY		ASING USED:			Wrought iron		Concrete tile	CASING JOINTS:		Clamped	
1		3 RMP (SR)			sbestos-Cem	•	Other (Specify	below)	Welded		
2 PVO		4 ABS			iberglass		DR-26		Threaded		
	asing Diam	-	in. to 25 .2		., Dia	in.	to lbs. / ft.	•	in. to	ft.	
	_	EN OR PERFORA		in. , [AL:	weight		PVC	Wall thickness or gauge No 10 Asbestos-		.214	
1 Ste		3 Stainless Steel			berglass		RMP (SR)	11 other (sp			
2 Bra	SS	4 Galvanized stee	el	6 Co	ncrete tile	9	ABS	` <b>-</b>	ed (open hole)		
SCREEN OR PERFORATION OPENING ARE: 5 Gauz.						uzed wrapped		8 Saw cut	11 None (open hole)		
1.6						re wrapped	9 Drilled holes				
2 Louve	ered shutte	r 4 Key pı	unched		7 Tor	ch cut		10 Other (specify)			
SCREEN-PERFORATION INTERVALS: from 25 ft. to 35 ft., From ft. to ft.											
			fron			ft. to	ft., Fro		to	ft.	
GRAVEL PACK INTERVALS: from 24					ft. to 35		ft., Fro		. to	ft.	
<u> </u>			fron	1		ft. to	ft., Fro	om ft	. to	ft.	
	OUT MAT			2 Cemen	t grout	3 Ben	tonite	4 Other			
Grout Intervals: From 4 ft. to 24 What is the nearest source of possible contamination:					ft. From	ft.	-	ft. From	ft. to	ft.	
1 Septic tank 4 Lateral li							10 Livestock pens 11 Fuel storage		14 Abandon water well		
7 Date in mics				8 Sewage lagoon				lizer storage	15 Oil well/Gas well		
2 Sewer lines 5 Cess pool 3 Watertight sewer lines 6 Seepage pit				9 Feedyard				ticide storage	16 Other (specify below)		
	n from we		age pit		) recuyatu						
FROM			LITHOLOGIC	LOG		FROM	то	How many feet? 75 PLUGGING IN			
0	3	topsoil									
3	11	clay									
11	21	fine san									
21	35	medium s	and								
				***							
							+				
							<del>                                     </del>		,		
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and											
was completed on (mo/day/year)											
Well C	ontracto	r's License No	236	This	Water Well	Record was co	ompleted on (	mo/day/yr)1 <i>2</i> .	/.18/.98		
Under the business name of Harp Well & Pump Service, Inc by (signature)  Todd & Harp											
ı								Joad	D. Th	arp	