

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: SEDGWICK		SW 1/4 SW 1/4 SE 1/4	17	T 26 S	R 1 E
Distance and direction from nearest town or city street address of well if located within city? 1/2 mile west of Broadway Ave. on 52nd Street, North side of Rd.					
2 WATER WELL OWNER:		Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box # :		Application Number:			
726 Minnesota		NA			
City, State, ZIP Code :					
Kansas City, KS 66101					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 44.0 ft. ELEVATION: 18.0 ft.			
		Depth(s) Groundwater Encountered 1. 18.0 ft. 2. 44.0 ft. 3. — ft.			
		WELL'S STATIC WATER LEVEL 14.25 ft. below land surface measured on mo/day/yr 7/27/97			
		Pump test data: Well water was — ft. after — hours pumping — gpm			
		Est. Yield — gpm: Well water was — ft. after — hours pumping — gpm			
		Bore Hole Diameter 8.0 in. to 44.0 ft. and — in. to — ft.			
		WELL WATER TO BE USED AS:			
		5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well MW-306 D			
		Was a chemical/bacteriological sample submitted to Department? Yes — No X ; If yes, mo/day/yr sample was submitted NA			
		Water Well Disinfected? Yes — No X			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued — Clamped —			
1 Steel 3 RMP (SR)		Welded —			
2 PVC 4 ABS		Threaded X			
Blank casing diameter 2 in. to 34.0 ft. Dia — in. to — ft. Dia — in. to — ft.					
Casing height above land surface 24.0 in., weight — lbs./ft. Wall thickness or gauge No. SCH. 40					
TYPE OF SCREEN OR PERFORATION MATERIAL:		10 Asbestos-cement			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR)		11 Other (specify) —			
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS		12 None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:		8 Saw cut 11 None (open hole)			
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes					
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) —					
SCREEN-PERFORATED INTERVALS: From 34.0 ft. to 44.0 ft. From — ft. to — ft.					
GRAVEL PACK INTERVALS: From 30.0 ft. to 44.0 ft. From — ft. to — ft.					
6 GROUT MATERIAL:		4 Other —			
1 Neat cement 2 Cement grout 3 Bentonite					
Grout Intervals: From 2.0 ft. to 30.0 ft. From — ft. to — ft. From — ft. to — ft.					
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well			
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)		Unknown			
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage					
Direction from well? —		How many feet? —			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0.0	8.0	Brown Silty clay			
8.0	27.0	Lt. Brown Silty clay to fine sand			
27.0	44.0	Medium Sand			
	44.0	Shale			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 1 constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7/15/97 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 602 This Water Well Record was completed on (mo/day/yr) 7/28/97 under the business name of Hydro-LOGIC, Inc. by (signature) <i>[Signature]</i>					