

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: SEDGWICK		SW 1/4 SW 1/4 SW 1/4	20	T 26 S	R 1 E/W
Distance and direction from nearest town or city street address of well if located within city? 49th and Arkansas Avenue					
2 WATER WELL OWNER: USE PA					
RR#, St. Address, Box # : 726 Minnesota			Board of Agriculture, Division of Water Resources		
City, State, ZIP Code : Kansas City, KS 66101			Application Number: NA		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 43.0 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. 19.0 ft. 2. — ft. 3. — ft.			
		WELL'S STATIC WATER LEVEL 7.98 ft. below land surface measured on mo/day/yr 7/27/97			
		Pump test data: Well water was — ft. after — hours pumping — gpm			
		Est. Yield — gpm: Well water was — ft. after — hours pumping — gpm			
		Bore Hole Diameter 8.0 in. to 43.0 ft., and — in. to — ft.			
		WELL WATER TO BE USED AS:			
		5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well M.W.-312D			
		Was a chemical/bacteriological sample submitted to Department? Yes — No X ; If yes, mo/day/yr sample was submitted NA			
		Water Well Disinfected? Yes — No X			
5 TYPE OF BLANK CASING USED:					
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued — Clamped — 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded — Blank casing diameter 2 in. to 33.0 ft., Dia — in. to — ft., Dia — in. to — ft. Casing height above land surface 24.0 in., weight — lbs./ft. Wall thickness or gauge No. SCH. 40 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) — 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes SCREEN-PERFORATED INTERVALS: From 33.0 ft. to 43.0 ft., From — ft. to — ft. GRAVEL PACK INTERVALS: From 29.0 ft. to 43.0 ft., From — ft. to — ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 2.0 ft. to 29.0 ft., From — ft. to — ft., From — ft. to — ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) unknown 13 Insecticide storage					
Direction from well? — How many feet? —					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0.0	12.0	Brown Silty Clay			
12.0	25.0	lt. Brown Silty Clay to Fine Sand			
25.0	43.0	Medium Sand			
		shale			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 1 constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7/17/97 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 602 This Water Well Record was completed on (mo/day/yr) 7/28/97 under the business name of Hydro-LOGIC, Inc. by (signature) <i>[Signature]</i>					