LOCATION OF WATER WELL:	FRACTION	Water Well Record	d Form WWC-5	KSA 82a-1212 Section Number	Township Number	Range Number
Sedgwick	SE 1/4	SE 1/4 I	NW 1/4	21		1 1 12
Distance and direction frem nearest town or ci			NW 1/4		т 26 в	I R IE E/W
_ 5018 N. Primros		ark City,	Vanga	a		
	NE, Allen	ark City,	<u> Kansa</u>	8	**	
	8 N. Primro	se			Board of Agriculture, D	divivsion of Water Resource
CITY, STATE, ZIP CODE: Par					er:	
LOCATE WELL'S LOCATION WITH	4 DEPTH OF COM	IPLETED WELL	50	ft. ELEV	VATION:	
AN "X" IN SECTION BOX:	Depth(s) groundwa	ater Encountered	1	ft.	2 ft.	3 ft.
	WELL'S STATIC W.		5 FT.	BELOW LAND SUR	FACE MEASURED ON mo/day/yr	03/02/1999
NE	Pump test	data: Well	water was	ft. a	fter hours pun	nping gpm
	Est. Yield	01	water was		fter hours pur	
E W	Bore Hole Diameter	12 in.	to 50	ft.	and in.	to ft.
	WELL WATER TO E 1 Domestic	BE USED AS: 3 Feedlot	5 Public water 6 Oil field wa		•	injection well
stwste	2 Irrigation	4 Industrial	7 Lawn and g		Monitoring well	Other (Specify below)
	Was a chemical/bacte				•	no/day/yr sample was
S	submitted	riologicai sample su	ibilitied to De	-	er Well Disinfected? Yes	
5 TYPE OF CASING USED:		5 Wrought iron	8	Concrete tile		Glued X Clamped
1 Steel 3 RMP (SR)		6 Asbestos-Ceme		Other (Specify bel		Velded
2 PVC 4 ABS		7 Fiberglass		DR-26	•	Threaded
Blank casing Diameter 5	in. to 30	ft., Dia	in.		ft., Dia in.	to ft.
Casing height above land surface		weight 2	.35	lbs. / ft. V	Vall thickness or gauge No.	.214
TYPE OF SCREEN OR PERFORA	TION MATERIAL:	£ Fil		PVC	10 Asbestos-cem	ent
1 Steel 3 Stainless Steel	_	5 Fiberglass		RMP (SR)	11 other (specify)
2 Brass 4 Galvanized ste		6 Concrete tile	9	ABS	12 None used (o)	•
SCREEN OR PERFORATION OPENING ARE:		5 Gauzed wrapped			8 Saw cut 11 None (open hole)	
1 Continous slot 3 Mill sl	6 Wire	6 Wire wrapped		9 Drilled holes		
2 Louvered shutter 4 Key p		7 Torcl	n cut		10 Other (specify)	
SCREEN-PERFORATION INTERV		ft.	to 50	ft., From	ft. to	ft.
from		ft. to		ft., From	ft. to	ft.
GRAVEL PACK INTERVALS: from 24		ft. to 50 ft. to		ft., From	ft. to	ft.
6 GROUT MATERIAL: 1 Neat		ement grout		ft., From	4 Other	ft.
Grout Intervals: From 4	ft. to 24	ft. From				A 40 A
What is the nearest source of possible contamination:		ft. From ft. to		10 Livestocl	ft. From k pens 14 A	ft. to ft. Abandon water well
1 Septic tank 4 Lateral lines		7 Pit privy		11 Fuel stor		Oil well/Gas well
2 Sewer lines 5 Cess pool		8 Sewage lagoon		12 Fertilize	er storage 16 (Other (specify below)
3 Watertight sewer lines 6 Seep	9 Feedyard	9 Feedyard 13 Insecticide storage		de storage		
Direction from well? East How many feet? 50						
	LITHOLOGIC LOG		FROM	то	PLUGGING INTE	RVALS
0 4 topsoil 4 12 clay				 		
4 12 clay 12 25 fine san			-	-		
	ine sand					
42 50 shale	THE BAHA		+			
7 CONTRACTOR'S OR LANDOWNE	R'S CERTIFICATION: Thi	s water well was (1) constructe	ed, (2) reconstruc	cted, or (3) plugged under n	ny jurisdiction and
was completed on (mo/day/year)	.J.J.J	and this rec	ord is true to the	best of my knowledge and	belief. Kansas Water
Well Contractor's License No Under the business name of.Ha	arp Well &	inis water well R Pump Servi	ice. In	ompleted on (mo	/uay/yr)	k./
CZCI LIIO MUGIIICOG HUITIC VIIARR	·····=			by (sigila	Todd L	. Harp