LICC	ATION OF W	ATER WELL:	FRACTION	Water Well Reco	ord Form WWC-5				
				377.7	47.7	Section Number	Township Number	Range Number	
Distance	Sedgy		NW 1/4		SW 1/4	19	т 26 s	R 1E E/W	
Distance and direction from nearest town or city street address of well if located within city? Meridian and Keywest St. Wichita, Kansas									
Meridian and Keywest St. Wichita, Kansas WATER WELL OWNER: WICHITA, CITY OF									
RR#, ST. ADRESS, BOX#: 455 N. Main Board of Agriculture, Divivsion of Water Resource									
CITY	Y, STATE, ZIP		hita, Kansa						
		LOCATION WITH	1	MPLETED WELL	45		EVATION:		
AN "X	" IN SECTIO	N BOX:	Depth(s) groundw	ater Encountered	1	ft.	2 ft.	3 ft.	
			WELL'S STATIC W		.2 FT.	BELOW LAND SUI	RFACE MEASURED ON mo/day/yr	03/15/1999	
	NW	NE	Pump test	t data: Well	water was	ft.	after hours pur	mping gpm	
ی ا			Est. Yield	01	water was	ft.	after hours pur		
M M	/k +	E	Bore Hole Diameter	12 in.	to 45	ft.	and in.		
			WELL WATER TO I	BE USED AS: 3 Feedlot	5 Public water		9	Injection well	
	sw	sie	1 Domestic 2 Irrigation	3 reediot 4 Industrial	6 Oil field wat 7 Lawn and g		9 Dewatering 12 10 Monitoring well	Other (Specify below)	
			1 "			-	G		
'		S	Was a chemical/bacte submitted	Piological sample s	ubmitted to De		No X; II yes, I ter Well Disinfected? Yes	mo/day/yr sample was X No	
5 TY	PE OF CA	SING USED:	to the second se	5 Wrought iron	8	Concrete tile		Glued Clamped	
1 Stee	el	3 RMP (SR)		6 Asbestos-Ceme		Other (Specify be		Welded Ciampeu	
2 PVC	C	4 ABS		7 Fiberglass		DR-26	•	Threaded	
Blank ca	 asing Diam	eter 8	in. to 20	ft., Dia	in.	to	ft., Dia in.	to ft.	
		ve land surface 1	L2 in.,	weight			Wall thickness or gauge No.	.332	
			TION MATERIAL:		•	PVC	10 Asbestos-cem		
1 Ste		3 Stainless Steel		5 Fiberglass		RMP (SR)	11 other (specif	y)	
						ABS	12 None used (o	• /	
l .		RFORATION OPI			ızed wrapped	8 Saw cut 11 None (open hole)			
ŀ	nous slot	3 Mill sl			e wrapped	9 Drilled holes			
	ered shutte	F		7 Toro			10 Other (specify)		
SCREEN-PERFORATION INTERVALS: from 20 ft. to 45						ft., From	ft. to	ft.	
					t. to	ft., From		ft.	
GRAVEL PACK INTERVALS: from 20					Nt. to 45	ft., From			
from ft. to ft., From ft. to ft. GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other									
Grout Intervals: From 0 9 to 20								ft. to ft.	
What is the nearest source of possible contamination:				IL FIOM	10 Lives		ft. From ck pens 14 /	ft. to ft. Abandon water well	
1 Septi	ic tank	4 Later	al lines	7 Pit privy		11 Fuel sto		Oil well/Gas well	
2 Sewer lines 5 Cess pool			pool	8 Sewage lagoon			ter storage 16	16 Other (specify below)	
3 Wate	rtight sewe	er lines 6 Seepa	age pit	9 Feedyard	9 Feedyard		cida etoroga	Apparent	
	n from wel					<u> </u>	How many feet?		
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS									
02	6	topsoil clay							
6	20	medium s	- na			-			
20	45	coarse s							
2	-	COSTSC D	Janu			<u> </u>			
 									
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year)									
Todd S. Harp									