Logi	TION OF III	TEN YOU .	ED 4 OTTON	Water Well Recor	d Form WWC-5		1	T	
1 LOCA	TION OF WA		FRACTION			Section Number	Township Number	Range Number	
-	Sedgw		NW 1/4		S W 1/4	19	T 26 s	R 1E E/W	
Distance and direction frem nearest town or city street address of well if located within city?									
Meridian and Keywest St. Wichita, Kansas WATER WELL OWNER: WICHITA, CITY OF									
	TER WELL C ST. ADRESS,		-	OF			Roard of Agriculture, D	livivsion of Water Resource	
i	, STATE, ZIP		N. Main hita, Kansa	nsas 67203			Application Number: 990047		
		OCATION WITH		MPLETED WELL	45		VATION:	r 990047	
	" IN SECTION		Depth(s) groundw		1	ft.	2 ft.	3 ft.	
t		- \ 	WELL'S STATIC W		_		FACE MEASURED ON mo/day/yr	03/15/1999	
			Pump tes		water was		after hours pum	•	
'	NW	NE	Est. Yield		water was		after hours pum		
1 Mile			Bore Hole Diameter	12 in.	to 45	ft.	and in.	to ft.	
= "	×	I I	WELL WATER TO		5 Public wate	r supply	8 Air conditioning 11 I	njection well	
1.		se	1 Domestic	3 Feedlot	6 Oil field wa	ter supply	9 Dewatering 12 0	Other (Specify below)	
	3W		2 Irrigation	4 Industrial 7 Lawn and garden only 10 Monitoring well					
Was a chemical/bacteriological sample submitted to Department? Yes						No X; If yes, n	no/day/yr sample was		
		S	submitted			Wat	er Well Disinfected? Yes	X No	
5 TYPE OF CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped									
1 Stee	ì	3 RMP (SR)		6 Asbestos-Ceme	ent 9	Other (Specify be	,	Velded	
2 PVC	2	4 ABS		7 Fiberglass	S	DR-26	7	Threaded	
	sing Diam	•	in. to 20	ft., Dia	in.	to	ft., Dia in.	to ft.	
Casing height above land surface 12 in., weight 5.52 lbs./ft. Wall thickness or gauge No332 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement									
1 Stee		3 Stainless Steel	TION MATERIAL:	5 Fiberglass		PVC RMP (SR)	11 other (specify		
2 Bras			al .	6 Concrete tile		ABS			
9 Samuel Steel								11 None (open hole)	
Scauze wrapped								11 None (open note)	
The state of the s									
1				7 Torc		.	12 2,	ft.	
SCREEN-PERFORATION INTERVALS: from 20					. to 45	ft., From	ft. to		
GRAVEL PACK INTERVALS: from 20					. to L to 4.5	ft., From ft., From		ft.	
				_	. to	ft., From		ft. ft.	
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other									
Grout In	itervals:]	From ()	ft. to 20	ft. From	ft.	to	ft. From	ft. to ft.	
What is	the nearest	source of possible	e contamination:			10 Livesto		bandon water well	
1 Septi	ic tank	4 Later	al lines	7 Pit privy		11 Fuel sto	13,	Oil well/Gas well	
2 Sewe		5 Cess	pool	8 Sewage lagoon		12 Fertiliz		Other (specify below)	
3 Wate	rtight sewe	r lines 6 Seep	age pit	9 Feedyard		13 Insection	13 Insecticide storage None Apparent		
Direction from well? How many feet?									
FROM	ТО		LITHOLOGIC LOG		FROM	TO	PLUGGING INTE	RVALS	
0 2	6	topsoil clay							
6	20	medium s	and						
20	45	coarse s							
	* -	COULDE	74114						
—									
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and									
was completed on (mo/day/year)									
Well Contractor's License No236									
Under	the busir	iess name of.ಗಸ	**************************************	Emmbyerx	₩₩ <u>₩</u> ₩₩	Am by (sign	ature)	Hann	
Todd S. Harp									