

1 LOCATION OF WATER WELL: Fraction 1/4 SE 1/4 SE 1/4 Section Number 16 Township Number T 26 S Range Number R 1E EW

Distance and direction from nearest town or city street address of well if located within city? 53rd & Broadway

2 WATER WELL OWNER: WBCater

RR#, St. Address, Box #: 6015 N. Broadway

City, State, ZIP Code: Wichita, KS 67229

Board of Agriculture, Division of Water Resources

Application Number: 990055

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

4 DEPTH OF COMPLETED WELL: 32 ft. ELEVATION: 5-7-99

Depth(s) Groundwater Encountered: 1. 9 ft. 2. 32 ft. 3. 5-7-99 ft.

WELL'S STATIC WATER LEVEL: 9 ft. below land surface measured on mo/day/yr

Pump test data: Well water was 30 gpm: Well water was 32 ft. after 32 hours pumping 32 gpm

Est. Yield 30 gpm: Well water was 32 ft. after 32 hours pumping 32 gpm

Bore Hole Diameter: 12 in. to 32 ft. and 32 in. to 32 ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well

1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes. No. X If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED:

1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped

2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded

Blank casing diameter 8 in. to 22 ft. Dia. 2.40 in. to 2.40 ft. Dia. 160psi

Casing height above land surface 12 in. weight 2.40 lbs./ft. Wall thickness or gauge No. 160psi

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement

2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)

2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes

7 Torch cut 32 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 22 ft. to 32 ft. From 9 ft. to 32 ft.

GRAVEL PACK INTERVALS: From 9 ft. to 32 ft.

6 GROUT MATERIAL: 3 1 Neat cement 9 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 3 ft. to 9 ft. From 3 ft. to 9 ft.

What is the nearest source of possible contamination:

1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well

2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well

3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)

13 Insecticide storage 14 Abandoned water well

Direction from well? How many feet?

FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS

0 2 topsoil

2 9 clay

9 32 sand

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5-7-99 and this record is true to the best of my knowledge and belief. Kansas

Water Well Contractor's License No. 318 This Water Well Record was completed on (mo/day/yr) 5-7-99

under the business name of Weneringer Drilling Inc. by (signature) Michelle Gorges

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.