

1) LOCATION OF WELL: Fraction: SW 1/4 SW 1/4 NW 1/4 Section Number: 19 Township Number: 26S Range Number: 10E  
County: Sedgwick  
Distance and Direction from nearest town or city street address of well if located within city?  
1/2 South of 53rd N & Meridian

2) WATER WELL OWNER: Earl Mies  
RR#, St. Address, Box #: 1919 S. Southwest Blvd.  
City, State, ZIP Code: Wichita, KS 67213  
Board of Agriculture, Division of Water Resources  
Application Number:

3) LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  
N  
NW NE  
X  
SW SE  
S  
W E

4) DEPTH OF COMPLETED WELL: 34 ft. ELEVATION:  
Depth(s) Groundwater Encountered: 1. ft. 2. ft. 3. ft.  
WELL'S STATIC WATER LEVEL: 14 ft. below land surface measured on mo/day/yr 7-1-99  
Pump test data: Well water was ft. after hours pumping gpm  
Est. Yield: 30 gpm Well water was ft. after hours pumping gpm  
Bore Hole Diameter: 11 in. to 34 in. to ft. and in. to ft.  
WELL WATER TO BE USED AS:  
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)  
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well  
Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted  
Water Well Disinfected? Yes X No

5) TYPE OF BLANK CASING USED:  
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped  
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded  
Blank casing diameter: 8 in. to 24 in. Dia. 2.40 in. to ft. Dia. in. to ft.  
Casing height above land surface: 12 in. weight lbs./ft. Wall thickness or gauge No. 160 psi  
TYPE OF SCREEN OR PERFORATION MATERIAL:  
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement  
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)  
12 None used (open hole)  
SCREEN OR PERFORATION OPENINGS ARE:  
1 Continuous slot 13 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)  
2 Louvered shutter 4 Key punched 7 Torch cut 9 Drilled holes  
SCREEN-PERFORATED INTERVALS: From 24 ft. to 34 ft. From ft. to ft.  
GRAVEL PACK INTERVALS: From 14 ft. to 34 ft. From ft. to ft.  
From ft. to ft. From ft. to ft.

6) GROUT MATERIAL: 3 1 Neat cement 14 2 Cement grout 3 Bentonite 4 Other  
Grout Intervals: From 3 ft. to 14 ft. From ft. to ft. From ft. to ft.  
What is the nearest source of possible contamination:  
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well  
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well  
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)  
13 Insecticide storage  
Direction from well? How many feet?  
pin field

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	topsoil			
2	17	clay			
17	34	fine to med. sand			

7) CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7-1-99 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 318 This Water Well Record was completed on (mo/day/yr) 7-1-99 under the business name of Wening Drilling Inc. by (signature) Michael Gorges

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.