L OG TION OF	WATER MAY	ED ACTION	Water Well Re	ecord Form WWC-5			T	
1 LOCATION OF		FRACTION	NTM	CITAT 411	Section Number	Township Number	Range Number	
Sedgwick NW  Distance and direction frem nearest town or city street address of			NW 1/4	SW 1/4	19	T 26 s	R 1E E/W	
	ian and Ke		•	ichita,	Kansas			
WATER WEL		HITA, CITY		ICHILLA,	Ransas			
RR#, ST. ADRE	1120.	N. Main	01			Board of Agriculture, l	Divivsion of Water Resource	
CITY, STATE, ZIP CODE: Wichita, Kans			as	s 67202		Application Numb	Application Number: 990047	
	S LOCATION WITH	4 DEPTH OF 🕏		L 45	ft. EI	EVATION:		
AN "X" IN SECT	ION BOX:	Depth(s) groundw	vater Encountere	d 1	ft.	2 ft.	3 ft.	
		WELL'S STATIC W	_	T 2	. BELOW LAND S	URFACE MEASURED ON mo/day/yr	07/16/1999	
NV	vNE	Pump tes		ell water was	ft.	after hours pun		
<u> </u>		Est. Yield	81	ell water was	ft.	after hours pun		
₩ w	E	Bore Hole Diameter WELL WATER	In.	to 5 Public wate	ft. r sunnly	and in. 8 Air conditioning 11	to ft. Injection well	
		1 Domestic	3 Feedlot	6 Oil field wa		•	Other (Specify below)	
sv	/SE	2 Irrigation	4 Industrial	7 Lawn and g		10 Monitoring well	(- <b>Fy</b> ,	
		Was a chemical/bacte	eriological sample	e submitted to De	epartment? Yes	=	no/day/yr sample was	
	S	submitted			_	ater Well Disinfected? Yes		
5 TYPE OF C	CASING USED:		5 Wrought ir	on 8	Concrete tile	CASING JOINTS: (	Glued Clamped	
1 Steel	3 RMP (SR)		6 Asbestos-Ce	ement 9	Other (Specify	below)	Welded	
2 PVC	4 ABS		7 Fiberglass			•	Threaded	
Blank casing Dia		in. to	ft., Dia			ft., Dia in.	to ft.	
	EEN OR PERFORA		weight		lbs. / ft. 7 PVC	Wall thickness or gauge No. 10 Asbestos-cem	ient	
5 Fibergless 9 DMD (SD) 44 Ab (mails)								
2 Brass 4 Galvanized steel 6 Concrete tile					9 ABS 12 None used (open hole)			
SCREEN OR P	ERFORATION OP	ENING ARE:	5 G	auzed wrapped	95			
1 Continous slo	t 3 Mill s	lot		ire wrapped				
2 Louvered shut	tter 4 Key p	unched	7 Te	orch cut		10 Other (specify) N	/A	
SCREEN-PERFORATION INTERVALS: from ft. to ft., From ft. to ft.								
		from		ft. to	ft., Fro	m ft. to	ft.	
GRAVEL PACK INTERVALS: from			ft. to		ft., Fro	om ft. to	ft.	
1	4 By 4	from		ft. to	ft., Fro			
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other bentonite hole plug								
Grout Intervals: From 3 ft. to 8 What is the nearest source of possible contamination:			ft. From ft. to		ft. From 8 tock pens 14	ft. to 12 ft. Abandon water well		
1 Septic tank 4 Lateral lines					11 Fuels		Oil well/Gas well	
2 Sewer lines 5 Cess pool			8 Sewage lagoon		12 Ferti	Fertilizer storage 16 Other (specify below)		
3 Watertight se		9 Feedyard 13 Inse			cticide storage None Apparent			
Direction from well?  How many feet?								
FROM TO		LITHOLOGIC LOG		FROM	ТО	PLUGGING INTE	RVALS	
				0	3	surface		
				3	8	cement grout		
				8 12	12 45	bentonite hole chlorinated sar		
					33	CHIOIIHACEG BAI	id alid graver	
-					.			
						A STATE OF THE STA		
7 CONTRACT	TODIS on the second	enie gentiuigation. Th	ie water well	ac (1) construct	ad (2) recens	tructed or (3) plugged under	my jurisdiction and	
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year)								
Well Contrac	tor's License No	<u> 236</u>	This Water We	II Record was o	ompleted on (	mo/day/yr)0.7./.1	9/99	
Under the bu	Under the business name of Harp Well & Pump ServiceInc by (signature)							
Todd S. Harp								